


Power lock industrial grade locking devices

Product description


3-pole, 4-wire grounding
20A, 250V/DC; 30A, 600V/AC
Non-NEMA




20414N



20415S



AH21420



21447

Industrial grade plugs & connectors



A	Rating V/DC	V/AC	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.	
20/ 30	250	600	Auto grip nylon	0.44-1.06" (11.1-26.0mm)	GY	□ 20415N	□ 20414N	•
			Armored w/ sliding rubber cord grip	0.36-0.48" (9.1-12.3mm)	Steel	□ 21415	□ 21414	
			Armored w/ sliding rubber cord grip	0.48-0.75" (12.3-19.1mm)	Steel	□ 21426	□ AH21427	
			Armored w/ sliding rubber cord grip & special mounting stud [†]	0.48-0.75" (12.3-19.1mm)	Steel	□ 21426S	—	
			Armored w/ sliding rubber cord grip	0.56-1.00" (14.3-25.4mm)	Steel	□ 20415	□ 20414	•
			Armored w/ sliding rubber cord grip & special mounting stud [†]	0.56-1.00" (14.3-25.4mm)	Steel	□ 20415S	—	•
			Armored female	0.75" (19.1mm)	Steel	□ AH21436	—	
			Armored female	0.75" (19.1mm)	Steel	—	□ 21434 ^{††}	

[†]Used in automotive welding applications, ^{††}Only UL Listed

Industrial grade receptacles



A	Rating V/DC	V/AC	Description	Color	Single receptacle	
20/ 30	250	600	Receptacles	BK	□ 20403N	•
			In angled cast aluminum cover w/ weather protective life lid	BK	□ AH21420	

Industrial grade inlets



A	Rating V/DC	V/AC	Description	Color	Inlet catalog no.
20/ 30	250	600	Inlet for FS/FD boxes	BK	□ 20418
			Angled surface mount w/ weather protective lift lid tapped for 0.75" (19.1mm) pipe thread, diecast aluminum		□ 21447

Accessories for 50A locking devices & power lock devices in FS/FS boxes

Description	Color	Catalog no.
Glass-filled nylon lift lid cover for 50A locking devices	Y	□ 7788CR
Glass-filled nylon lift lid cover for 4-wire 30A receptacles	GY	□ 20416N [†]

[†]Only CSA and UL Listed



7788CR



20416N

Dimensional information:
C-82, C-83

Plug & connector specification information:
Power lock: C-94

Receptacle specification information:
Power lock: C-95

Inlet specification information:
Power lock: C-94

Color information:

BK (Black), GY (Gray)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-30