Sealed Sensor Connector SSC System

TE Internal #: 2-936060-1

Wire-to-Device / Wire-to-Board, 3 Position, .197 in [5 mm]


Centerline, Sealable, Black, Signal, Sealed Sensor Connector SSC

System

View on TE.com >



Connectors > Automotive Connectors > Connector Housings



Mating Tab Width: 2.8 mm [.11 in]

Connector System: Wire-to-Board, Wire-to-Device

Number of Positions: 3

Centerline (Pitch): 5 mm [.197 in]

Sealable: Yes

Features

Product Type Features

Connector & Housing Shape	Rectangular
Connector System	Wire-to-Board, Wire-to-Device
Sealable	Yes
Hybrid Connector	No
Configuration Features	
Number of Positions	3
Number of Rows	1
Body Features	
Body Material	PA GF
Primary Product Color	Black
Connector Code	III
Contact Features	

Contact Features

Contact Size	2.8mm
Mating Tab Width	2.8 mm[.11 in]

Mechanical Attachment

Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Keyed



Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	5 mm[.197 in]
Dimensions	
Product Width	20.1 mm[.791 in]
Product Length	30 mm[1.181 in]
Product Height	30.5 mm[1.201 in]
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Quantity	150
Packaging Method	Bag
Other	
Serviceable	No
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as



EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts


















Also in the Series | Sealed Sensor Connector SSC System







Automotive Connector Locks & Position Assurance(6)



Automotive Housings(178)






Automotive Terminals(8)



Insertion & Extraction Tools(1)



Other Automotive Connector Accessories(7)



Customers Also Bought













Documents

Product Drawings

2.8MM SLD 3P PLUG ASSY

English

CAD Files

Customer View Model

ENG_CVM_CVM_2-936060-1_C.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-936060-1_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-936060-1_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

2.8MM SENSOR FLAT TYPE RECEPTACLE CONTACT SYSTEM

English

Application Specification

English

Wire-to-Device / Wire-to-Board, 3 Position, .197 in [5 mm] Centerline, Sealable, Black, Signal, Sealed Sensor Connector SSC System

