

AMP | AMP M Series

TE Internal #: 205690-2

Rectangular Power Connectors, Housing, Receptacle, Cable-to-Cable / Cable-to-Panel, 28 Position, .25 in [6.35 mm] Centerline,

AMP M Series

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Housing

Connector & Housing Type: Receptacle

Connector System: Cable-to-Cable, Cable-to-Panel

Number of Positions: 28

Centerline (Pitch): 6.35 mm [.25 in]

Features

Product Type Features

| 1 Toduct Type Features | |
|-----------------------------------|--------------------------------|
| Rectangular Power Connector Type | Housing |
| Connector & Housing Type | Receptacle |
| Connector System | Cable-to-Cable, Cable-to-Panel |
| Sealable | No |
| Connector & Contact Terminates To | Wire & Cable |
| Configuration Features | |
| Number of Positions | 28 |
| Number of Power Positions | 28 |
| Number of Signal Positions | 28 |
| Number of Rows | 4 |
| Electrical Characteristics | |
| Operating Voltage | 1800 VDC |
| Contact Features | |

13 A

Contact Current Rating (Max)



| Contact Retention Within Housing | With |
|------------------------------------|-------------------------------|
| Contact Type | Socket |
| Termination Features | |
| Termination Method to Wire & Cable | Crimp |
| Mechanical Attachment | |
| Panel Mount Feature | With |
| Panel Mount Feature Type | Screw Mount |
| Connector Mounting Type | Panel Mount |
| Housing Features | |
| Centerline (Pitch) | 6.35 mm[.25 in] |
| Housing Color | Black |
| Housing Material | Phenolic |
| Dimensions | |
| Wire Size | $.05 - 2 \text{ mm}^2$ |
| Row-to-Row Spacing | 6.35 mm[.25 in] |
| Height | 65.91 mm[2.595 in] |
| Length | 28.45 mm[1.12 in] |
| Width | 28.19 mm[1.11 in] |
| Usage Conditions | |
| Operating Temperature Range | -55 – 150 °C[-67 – 302 °F] |
| Operation/Application | |
| Circuit Application | Power & Signal |
| Industry Standards | |
| UL Flammability Rating | UL 94V-0 |
| Glow Wire Rating | Standard Part - Not Glow Wire |
| Packaging Features | |
| Packaging Method | Package |
| Packaging Quantity | 1 |
| Other | |
| For Use With | Standard 75 Position Hardware |
| | |



Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Wave solder capable to 265°C |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | AMP M Series





Board-to-Board Jumpers & Shunts(7)



Rack & Panel Connectors(1)



Rectangular Connector Hardware (52)



Rectangular Power Connectors(69)



Customers Also Bought






TE Part #1-201046-2
SERIES "M" MIN RECT GUIDE PIN



TE Part #2-1419106-4 27E892=SOCKET,KRPA,11,OCTAL,PO









TE Part #205269-1 ASY, JACKSCREW-FEMALE

Documents

Product Drawings
SOC. BLOCK 28 POS. SPL.

English

CAD Files

Customer View Model ENG_CVM_CVM_205690-2_M.3d_stp.zip

English

Customer View Model



ENG_CVM_CVM_205690-2_M.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_205690-2_M.3d_igs.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

M_SERIES_PIN_AND_SOCKET_CONNECTORS

English

Product Environmental Compliance

TE Material Declaration

English

Agency Approvals

Agency Approval Document

English

Agency Approval Document

English