2029111-3 ACTIVE

VAL-U-LOK

TE Internal #: 2029111-3

Rectangular Power Connectors, Housing, Plug, Wire-to-Wire, 3 Position, .165 in [4.2 mm] Centerline, Wire & Cable, UL 94V-2, GWT

750°C (Without Flame)

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Housing

Connector & Housing Type: Plug
Connector System: Wire-to-Wire

Number of Positions: 3

Centerline (Pitch): 4.2 mm [.165 in]

Features

Product Type Features

| Product Type Features | |
|-----------------------------------|--------------|
| Rectangular Power Connector Type | Housing |
| Connector & Housing Type | Plug |
| Connector System | Wire-to-Wire |
| Sealable | No |
| Connector & Contact Terminates To | Wire & Cable |
| Configuration Features | |
| Number of Positions | 3 |
| Number of Rows | 1 |
| Electrical Characteristics | |
| Operating Voltage | 600 VAC |
| Contact Features | |
| Contact Layout | Inline |
| Contact Retention Within Housing | Without |

Pin

Contact Type



| Termination Features | |
|--|------------------------------|
| Termination Method to Wire & Cable | Crimp |
| Wire/Cable Type | Discrete Wire |
| Mechanical Attachment | |
| Connector Mounting Type | Cable Mount (Free-Hanging) |
| Housing Features | |
| Centerline (Pitch) | 4.2 mm[.165 in] |
| Housing Color | White |
| Housing Material | Nylon 66 |
| Dimensions | |
| Width | 23.9 mm[.94 in] |
| Accepts Wire Insulation Diameter Range | 1.2 – 3.1 mm[.047 – .122 in] |
| Height | 7.4 mm[.291 in] |
| Length | 13.8 mm[.543 in] |
| Usage Conditions | |
| Operating Temperature Range | -40 - 105 °C[-40 - 221 °F] |
| Operation/Application | |
| Circuit Application | Power & Signal |
| Identification Marking | |
| Circuit Identification Feature | With |
| Industry Standards | |
| UL Flammability Rating | UL 94V-2 |
| Glow Wire Rating | GWT 750°C (Without Flame) |
| Agency/Standard Number | E28476 |
| Agency/Standard | CSA, UL |
| UL Rating | Recognized |
| CSA File Number | 208567 |
| Packaging Features | |
| Packaging Method | Bag |
| Packaging Quantity | 1000 |



Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Not applicable for solder process capability |


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts



















Customers Also Bought














Documents

Product Drawings 3P PLUG SR VAL-U-LOK FH GW

English

CAD Files

Customer View Model

ENG_CVM_2029111-3_A.3d_igs.zip

English

Customer View Model

ENG_CVM_2029111-3_A.3d_stp.zip

English

Customer View Model

ENG_CVM_2029111-3_A.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

VAL-U-LOK_GLOW_WIRE_CONNECTORS

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Rectangular Power Connectors, Housing, Plug, Wire-to-Wire, 3 Position, .165 in [4.2 mm] Centerline, Wire & Cable, UL 94V-2, GWT 750°C (Without Flame)



MD_2029111-3_06132018949_dmtec

English

MD_2029111-3_06132018949_dmtec

English

Agency Approvals

UL Report

English