2-917542-2 ACTIVE

Dynamic Series | Dynamic 5000 Series

TE Internal #: 2-917542-2

PCB Mount Header, Vertical, Wire-to-Board, 4 Position, .4 in [10.16 mm] Centerline, Fully Shrouded, Gold, Through Hole - Solder,

Dynamic 5000 Series

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > Header Assembly: Wire-to-Board, 20-45A, 250-630V



Connector System: Wire-to-Board

Number of Positions: 4
Number of Rows: 1

Centerline (Pitch): 10.16 mm [.4 in]
PCB Mount Orientation: Vertical

All Header Assembly: Wire-to-Board, 20-45A, 250-630V (59)

Features

Product Type Features	
Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header
Configuration Features	
Number of Positions	4
Number of Rows	1
PCB Mount Orientation	Vertical
Body Features	
Primary Product Color	Black
Contact Features	
Contact Mating Area Plating Material Thickness	.38 μm[15 μin]
Contact Mating Area Plating Material	Gold

Pin

30 A

Contact Type

Contact Current Rating (Max)



Termination Features

Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Keyed
Mating Retention	With
PCB Mount Retention Type	Retention Leg
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	With
Housing Features	
Housing Material	Polyester GF
Centerline (Pitch)	10.16 mm[.4 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	

Product Compliance

Packaging Type

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Box, Tube



Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Dynamic 5000 Series

& Housings(71)



Customers Also Bought

PCB Mount Header, Vertical, Wire-to-Board, 4 Position, .4 in [10.16 mm] Centerline, Fully Shrouded, Gold, Through Hole - Solder, Dynamic 5000 Series





TE Part #2-179960-2 DYNAMIC D-5200 HDR ASSY 6P V Y



TE Part #1827525-1
MECHATROLINK II CONNECTOR KIT



TE Part #1-338070-0 MICRO-MATCH FEM.SE



TE Part #8-1879215-3 CPF 0402 33K2 0.1% 25PPM 1K RL



TE Part #5-1879267-0 RP 2B 1M0 0.1% 15PPM 1K RL



TE Part #1-770174-0 04P MINI-UMNL ASSY V0 SNNI*



TE Part #4-794634-6 16P MICRO MNL ASSY,VRT,SMT LF





Documents

Product Drawings

DYNAMIC D-5 S/ROW HDR ASY 4P V

Japanese

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_2-917542-2_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_2-917542-2_F.3d_igs.zip

English

Customer View Model

ENG_CVM_2-917542-2_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages



1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH

Japanese

1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH

English

Product Specifications

Product Specification

English

Product Environmental Compliance

MD_2-917542-2_11102017616_dmtec

English

MD_2-917542-2_11102017616_dmtec

English

Agency Approvals

TUV Certificate

English