2106003-1 ACTIVE

LUMAWISE | Insulation Displacement Connectors Closed End

TE Internal #: 2106003-1

Poke-In Connectors, Wire-to-Board, 1 Position, 4 in [.16 mm] Centerline, Printed Circuit Board, Insulation Displacement

Connectors Closed End

View on TE.com >



Connectors > Lighting Connectors > Poke-In Connectors











Connector System: Wire-to-Board

Number of Positions: 1

Centerline (Pitch): .16 mm [4 in]

Sealable: No

Connector & Contact Terminates To: Printed Circuit Board

Features

Product Type Features

Connector Type	Connector Assembly
Connector Style	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	1
Contact Features	
Contact Current Rating (Max)	8.5 A
Termination Features	
Termination Method to Printed Circuit Board	Surface Mount
Mechanical Attachment	

Board Mount

Connector Mounting Type



Housing Features

Centerline (Pitch)	.16 mm[4 in]
Dimensions	
Connector Height	.23 mm[5.8 in]
Wire Size	18 – 16 AWG
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Power

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # 2106431-1 Connector, SMT-IDC PASS THRU, 1 POS, 18

TE Part # 4-2106003-1 Connector, SMT-IDC,1 pos, 18AWG, black

Also in the Series | Insulation Displacement Connectors Closed End



Ballast Connectors(23)



PCB Headers & Receptacles(1)



Poke-In Connectors(66)

Customers Also Bought



TE Part #3-641191-4 Nylon Gold Plated Receptacle: 2.54 mm, No Mating Alignment, MTA 100



TE Part #3-641126-8 08P MTA100 HDR ASY FL/STR LF



TE Part #3-644563-4 04P MTA100 CONN ASSY F/T 24AWG



TE Part #2-2176057-7 RLP73K 3A R12 1% 1K RL



TE Part #3-641120-2 02P MTA156 HDR ASSY FL/ST LF




TE Part #4-1879021-7 SMW3 8R2 5%



TE Part #8-215460-0 MICRO-MATCH FSID P



JACK,DECOUPLER,R/A,75 OHM, BNC





Documents

Product Drawings

Connector, SMT-IDC, 1 POS, 18 AWG

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2106003-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2106003-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2106003-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

IDC_SSL_CONNECTOR

English

Product Specifications

Application Specification

English

Product Environmental Compliance

TE Material Declaration

English

Agency Approvals

Agency Approval Document

English