

AMP | LEAVYSEAL

TE Internal #: 2112045-1

Other Automotive Connector Accessories, Mounting Clips, Wire-to-

Wire, PA GF, Red, -40 – 130 °C [-40 – 266 °F], LEAVYSEAL

View on TE.com >



Connectors > Automotive Connectors > Connector Accessories > Other Connector Accessories > LEAVYSEAL LOCKING SLIDES











Automotive Connector Accessory Type: Mounting Clips

Connector System: Wire-to-Wire
Primary Product Material: PA GF
Primary Product Color: Red

Operating Temperature Range: -40 - 130 °C [-40 - 266 °F]

All LEAVYSEAL LOCKING SLIDES (7)

Features

Product Type Features

Automotive Connector Accessory Type Connector System Wire-to-Wire Body Features Primary Product Material PA GF Primary Product Color Red Usage Conditions Compatible With Connector Style Operating Temperature Range UL Flammability Rating UL 94V-0 Packaging Features		
Body Features Primary Product Material Primary Product Color Red Usage Conditions Compatible With Connector Style Operating Temperature Range Industry Standards UL Flammability Rating UL 94V-0	Automotive Connector Accessory Type	Mounting Clips
Primary Product Material PA GF Red Usage Conditions Compatible With Connector Style Operating Temperature Range Industry Standards UL Flammability Rating PA GF Red Wed Red Usage Conditions Usage Condi	Connector System	Wire-to-Wire
Primary Product Color Usage Conditions Compatible With Connector Style Operating Temperature Range Industry Standards UL Flammability Rating Red Housing For Male Terminals -40 – 130 °C[-40 – 266 °F] UL 94V-0	Body Features	
Usage Conditions Compatible With Connector Style Housing For Male Terminals Operating Temperature Range -40 – 130 °C[-40 – 266 °F] Industry Standards UL Flammability Rating UL 94V-0	Primary Product Material	PA GF
Compatible With Connector Style Operating Temperature Range -40 – 130 °C[-40 – 266 °F] Industry Standards UL Flammability Rating UL 94V-0	Primary Product Color	Red
Operating Temperature Range -40 – 130 °C[-40 – 266 °F] Industry Standards UL Flammability Rating UL 94V-0	Usage Conditions	
Industry Standards UL Flammability Rating UL 94V-0	Compatible With Connector Style	Housing For Male Terminals
UL Flammability Rating UL 94V-0	Operating Temperature Range	-40 – 130 °C[-40 – 266 °F]
	Industry Standards	
Packaging Features	UL Flammability Rating	UL 94V-0
Tuekaging Features	Packaging Features	

750

Box

Packaging Quantity

Packaging Method



Other

Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | LEAVYSEAL





Automotive Connector Caps & Covers (16)




Automotive Housings(64)



Insertion & Extraction Tools(5)



Other Automotive Connector Accessories(15)



PCB Headers & Receptacles(13)

Customers Also Bought



TE Part #1-2112041-2 26POS, MIXED,TAB HSG,ASSY, SEALED



TE Part #1-2141846-1 CARRIER,RECEPTACLE HSG, 25POS, ASSY



TE Part #284436-1 COVER FOR 40 POS. FEMALE HSG



TE Part #284371-1 COVER FOR PLATE



TE Part #284581-1
SUPPORT PLATE ASSEMBLY

TE Part #10142034-00 HTM2500B6C6IV RH/T MODULE DATA MATRIX-2

TE Part #1703768-2 14POS,AMP MCP1.5K,SOCK HSG, ASSY,12POS TE Part #284366-3 40 POS. MALE CONN. ASSY -YELLO

TE Part #FPP146-00056 RUBBER GASKET QLS TZIRQ TE Part #284352-1

Documents



Product Drawings

SLIDE, FOR 26POS TAB HSG

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2112045-1_A_c-2112045-1-a.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2112045-1_A_c-2112045-1-a.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2112045-1_A_c-2112045-1-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

German