
284423-7 - ACTIVE

AMP | MQS

TE Internal #: 284423-7 Housing for Female Terminals, Wire-to-Wire, 32 Position, .1 in [2.54 mm] Centerline, White, Signal, Cable Mount (Free-Hanging), MQS View on TE.com >

Connectors > Automotive Connectors > Connector Housings > MQS, CONNECTOR HOUSING



Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: .64 mm [.025 in]

Connector System: Wire-to-Wire

Number of Positions: 32

Centerline (Pitch): 2.54 mm [.1 in]

All MQS, CONNECTOR HOUSING (557)

Features

Product Type Features

Connector & Housing Shape

Connector & Housing Type

Rectangular

Housing for Female Terminals



Connector System	Wire-to-Wire
Sealable	No
Hybrid Connector	No
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	32
Number of Rows	2
Electrical Characteristics	
Operating Voltage	24 VDC
Nominal Voltage Architecture	12 V, 24 V
Body Features	
Cable Exit Angle	90°
Body Material	PAGF
Primary Product Color	White
Contact Features	

Housing for Female Terminals, Wire-to-Wire, 32 Position, .1 in [2.54 mm] Centerline, White, Signal, Cable Mount (Free-Hanging), MQS



Contact Size	.63mm	
Contact Type	Receptacle	
Mating Tab Width	.64 mm[.025 in]	
Mechanical Attachment		
Mounting Feature	Without	
Terminal Position Assurance	No	
Strain Relief	Without	
Mating Alignment Type	Polarized	
Mating Alignment	With	
Connector Mounting Type	Cable Mount (Free-Hanging)	
Housing Features		
Centerline (Pitch)	2.54 mm[.1 in]	
Dimensions		
Product Width	17.6 mm[.693 in]	
Product Length	48.3 mm[1.902 in]	
Product Height	39.9 mm[1.571 in]	
i ioduct neight		

Usage Conditions

Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C[158 °F][167 °F][176 °F][185 °F][194 °F] [212 °F][221 °F]	
Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]	
Operation/Application		
Circuit Application	Signal	
Packaging Features		
Packaging Method	Box	
Other		
Serviceable	No	
Connector Position Assurance Capable	No	
Product Compliance For compliance documentation, visit the product page on TE.com>		
EU RoHS Directive 2011/65/EU	Compliant	

C For support call+1 800 522 6752

Housing for Female Terminals, Wire-to-Wire, 32 Position, .1 in [2.54 mm] Centerline, White, Signal, Cable Mount (Free-Hanging), MQS



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | MQS



Housing for Female Terminals, Wire-to-Wire, 32 Position, .1 in [2.54 mm] Centerline, White, Signal, Cable Mount (Free-Hanging), MQS







Customers Also Bought



TE Part #284223-4 24 POS.KIT ASSY FOR AIR BAG (B	TE Part #348793-3 SHORTING CONN RECPT HSG. ASSEM	TE Part #A88297-000 ES-CAP-HW-NO.1-X-35MM	TE Part #2005216-6 MCP 2.8 RETAINER HSG
TE Part #2005210-2 TCU 68P PLUG ASSY	TE Part #2005215-6 MQS RETAINER HSG FOR 68P	TE Part #2005327-1 025/090/110 HYB 24P PLUG ASSY	TE Part #2278598-3 12POS MOS REC
TE Part #2344391-1 43POS,MCON 1.2,REC HSG ASSY,SLD	TE Part #2357849-1 GWM VW AKII PIGTAIL Instead of GM		

Documents

AKII

Housing for Female Terminals, Wire-to-Wire, 32 Position, .1 in [2.54 mm] Centerline, White, Signal, Cable Mount (Free-Hanging), MQS



Product Drawings 32 POS KIT ASS'Y FOR AIR BAG

English

CAD Files

Customer View Model

ENG_CVM_284423-7_A4.3d_igs.zip

English

Customer View Model

ENG_CVM_284423-7_A4.3d_stp.zip

English

Customer View Model

ENG_CVM_284423-7_A4.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages Micro Quadlok Interconnection System (MQS)

English

Product Specifications Application Specification

English

Instruction Sheets Instruction Sheet (non U.S.)

English