

#### TH/.025 Connector System

TE Internal #: 2237126-2 Housing for Female Terminals, Wire-to-Board / Wire-to-Device, 4 Position, .087 in [2.2 mm] Centerline, Gray, Signal, TH/.025 Connector System

#### View on TE.com >





Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: .64 mm [.025 in ]

Connector System: Wire-to-Board, Wire-to-Device

Number of Positions: 4

Centerline (Pitch): 2.2 mm [.087 in ]

#### All TH/.025 CONNECTOR SYSTEM, HOUSING (202)



## Features

#### Product Type Features

Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Board, Wire-to-Device
Sealable	No
Hybrid Connector	No
Primary Locking Feature	Integrated in Housing
Configuration Features	
Number of Positions	4
Number of Rows	1
Electrical Characteristics	
Nominal Voltage Architecture	12 V
Body Features	

Housing for Female Terminals, Wire-to-Board / Wire-to-Device, 4 Position, .087 in [2.2 mm] Centerline, Gray, Signal, TH/.025 Connector System



Cable Exit Angle	180°
Body Material	PBT
Primary Product Color	Gray
Connector Code	2
Contact Features	
Contact Size	.64mm
Contact Type	Receptacle
Mating Tab Width	.64 mm[.025 in]
Mechanical Attachment	
Mechanical Attachment Mounting Feature	Without
	Without Yes
Mounting Feature	
Mounting Feature Terminal Position Assurance	Yes
Mounting Feature Terminal Position Assurance Strain Relief	Yes Without
Mounting Feature Terminal Position Assurance Strain Relief Mating Alignment Type	Yes Without Keyed

Centerline (Pitch)

2.2 mm[.087 in]

## Dimensions

Product Width	11.8 mm[.465 in]
Product Length	19 mm[.748 in]
Product Height	11 mm[.433 in]
Usage Conditions	
Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	100
Packaging Method	Bag
Other	

**C** For support call+1 800 522 6752

Housing for Female Terminals, Wire-to-Board / Wire-to-Device, 4 Position, .087 in [2.2 mm] Centerline, Gray, Signal, TH/.025 Connector System



Serviceable	Yes
Connector Position Assurance Capable	No
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





# Also in the Series | TH/.025 Connector System

**&** For support call+1 800 522 6752

Housing for Female Terminals, Wire-to-Board / Wire-to-Device, 4 Position, .087 in [2.2 mm] Centerline, Gray, Signal, TH/.025 Connector System







# Customers Also Bought



DEUTSCH DT Series Housings & Connectors

DEUTSCH DT WEDGELOCKS

AMP SUPERSEAL 1.5MM, CONNECTOR HOUSING

SINGLE WIRE SEAL



# Documents

Product Drawings 0.64II 4P 1ROW PLUG HOUSING KEY2
English
CAD Files 3D PDF
3D
Customer View Model ENG_CVM_CVM_2237126-2_1.2d_dxf.zip

**C** For support call+1 800 522 6752

Housing for Female Terminals, Wire-to-Board / Wire-to-Device, 4 Position, .087 in [2.2 mm] Centerline, Gray, Signal, TH/.025 Connector System



English

Customer View Model ENG\_CVM\_CVM\_2237126-2\_1.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2237126-2\_1.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Product Specification

English

Instruction Sheets Instruction Sheet (U.S.)

English