




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **4 – 5.2 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Terminates To	Wire & Cable
Wire/Cable Type	Regular Wire
Wire Stop	No
Insertion Force	Normal
Sealable	No

Configuration Features

Connection Capacity	Single
---------------------	--------

Electrical Characteristics

Voltage (Max)	250 V
---------------	-------

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	6.35 mm [.25 in]
Mating Tab Thickness	.81 mm [.032 in]
Terminal Orientation	Straight



Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Mechanical Attachment

Mating Retention Type	Locking Lance
Locking Lance Height	1.5 mm
Wire Insulation Support	With

Dimensions

Accepts Wire Insulation Diameter Range	3.4 – 5.2 mm [.134 – .205 in]
Receptacle Terminal Stock Thickness	.41 mm [.016 in]
Overall Length	30.1 mm [1.185 in]
Wire Size	4 – 5.2 mm ²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C [-40 – 230 °F]

Industry Standards

UL Flammability Rating	UL 94V-2
------------------------	----------

Packaging Features

Packaging Quantity	2500
Packaging Method	Strip/Reel

Other

Comment	Tab for crimping Tab Housing Part No. 927203., With locking hole.
---------	---

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224)



Candidate List Declared Against: JAN 2022
(223)
SVHC > Threshold:
Not Yet Reviewed

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 280074-2
FF 375 TAB 6-10MM2 PTBR



TE Part # 2-2150459-2
OCEAN_2.0_Applicator-E-160F210F



TE Part # 2150459-2
OCEAN_2.0_Applicator-E-160F210F



TE Part # 7-2150459-2
OCEAN_2.0_Applicator-E-160F210F



KIT
REPRESENTATION ONLY

TE Part # 7-2150459-7
OCEAN_2.0_SPARE_PART_KIT-160F210F

Also in the Series | **FASTIN-FASTON 250**




Crimp Terminal Housings(218)



Insertion & Extraction Tools(2)



PCB Terminals(2)




Quick Disconnects(255)

Customers Also Bought



TE Part #4-1703818-1
4POS,TAB 2.8X0.8,TAB HSG,ASSY,



TE Part #3-1437719-0
T01-0550-S03-FEMALE PLUG
CONNECTOR SOLDE



TE Part #W4SD
WEDGE LOCK, 4P, PLG, BRN, STD,
DT, D



TE Part #344271-1
3 WAY TAB HOUSING BLACK ECONO



TE Part #1924580-2
ASSEMBLY SOCKET LOOSE PC NICKE




TE Part #345208-1
070 SERIES RECEPT.



TE Part #344107-1
18W EMS.REC.ANTI-BACKOUT



TE Part #345255-1
ANTI-BACKOUT 3WAY TAB
HSGECONO



TE Part #345256-1
ANTI-BACKOUT 3WAY REC
HSGECONO



TE Part #925597-1
MIN-SPRING REC.

Documents

Product Drawings

[FF 250 TAB 4-6MM2 BR](#)

CAD Files

[3D PDF](#)

[3D](#)

Customer View Model

[ENG_CVM_CVM_280080-1_Z.2d_dxf.zip](#)

English



Customer View Model

[ENG_CVM_CVM_280080-1_Z.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_280080-1_Z.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[1654742_HOUSEHOLD_APPLIANCES_RAST5](#)

English

Product Specifications

[FASTIN-FASTON CONN. .110 INCH, .187 INCH, .250 INCH, .375 INCH SRS.](#)

English

Product Specification

English

Product Environmental Compliance

[Product Compliance](#)

English

[Product Compliance](#)

English