#### Buchanan

TE Internal #: 282862-4


PCB Terminal Blocks, Header, Wire-to-Board, 4 Position, .197 in [5 mm] Centerline, 1 Row, Top Wire Entry Angle, 30 – 12 AWG Wire

Size

View on TE.com >



Connectors > Terminal Blocks & Strips > PCB Terminal Blocks











Terminal Block Connector Type: Header

Connector System: Wire-to-Board

Number of Positions: 4

Centerline (Pitch): 5 mm [ .197 in ]

Number of Rows: 1

### **Features**

### **Product Type Features**

Wire Protection	With
Block Type	PCB Mount
Terminal Block Connector Type	Header
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	4
Number of Rows	1
Wire Entry Angle	Тор
Electrical Characteristics	
Current Rating (Max)	24 A
Voltage Rating	300 VAC
Contact Features	

Contact Mating Area Plating Material Tin



Contact Base Material	Brass
Contact Current Rating (Max)	24 A
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Housing Color	Green
Housing Material	PA 66
Centerline (Pitch)	5 mm[.197 in]
Dimensions	
PCB Tail Length	3.6 mm[.142 in]
Wire Size	$.05 - 3 \text{ mm}^2$
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	

Power & Signal

## **Product Compliance**

Circuit Application

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU  EU ELV Directive 2000/53/EC  Compliant with Exemptions  China RoHS 2 Directive MIIT Order No 32, 2016  EU REACH Regulation (EC) No. 1907/2006  Current ECHA Candidate List: JUNE 2022 (224)  Candidate List Declared Against: JAN 2022 (223)  SVHC > Threshold: Pb (.8% in Component Part)  Article Safe Usage Statements: Do not set, drink or smoke when using this product. Wash thoroughly after Inauling, Recycle Inpublic and dispose of the article by following all applicable governmental regulations relevant to your geographic location.  Hallogen Content  Low Hallogen - Br, CI, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free  Solder Process Capability  Wave solder capable to 265°C		
China RoHS 2 Directive MIIT Order No 32, 2016  EU REACH Regulation (EC) No. 1907/2006  Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Pb (.8% in Component Part) Artide Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling, Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.  Halogen Content  Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free	EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU REACH Regulation (EC) No. 1907/2006  Current ECHA Candidate List: JUNE 2022 (224)  Candidate List Declared Against: JAN 2022 (223)  SVHC > Threshold:  Pb (.8% in Component Part)  Article Safe Usage Statements:  Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.  Halogen Content  Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free	EU ELV Directive 2000/53/EC	Compliant with Exemptions
(224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Pb (.8% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.  Halogen Content  Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free	China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
homogenous material. Also BFR/CFR/PVC Free	EU REACH Regulation (EC) No. 1907/2006	(224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Pb (.8% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable
Solder Process Capability  Wave solder capable to 265°C	Halogen Content	homogenous material. Also BFR/CFR/PVC
	Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


# **Compatible Parts**







# **Customers Also Bought**



### **Documents**

**Product Drawings** 

TERMI-BLOK PCB MOUNT 180 4P.5

English

**Datasheets & Catalog Pages** 

**BUCHANAN TERMINAL BLOCKS CATALOG - EUROSTYLE TERMINAL BLOCKS** 

English

1-1773458-1\_EURO\_STYLE\_TERMINAL\_BLOCKS\_QRG

English

**Product Specifications** 

**Application Specification** 

English

PCB Terminal Blocks, Header, Wire-to-Board, 4 Position, .197 in [5 mm] Centerline, 1 Row, Top Wire Entry Angle, 30 – 12 AWG Wire Size

