#### Nano MQS

TE Internal #: 2303088-1

Housing for Female Terminals, 32 Position, .071 in [1.8 mm]

Centerline, Blue, Flexible Printed Circuit (FPC), Signal, Nano MQS

View on TE.com >




Connectors > Automotive Connectors > Connector Housings > MQS, CONNECTOR HOUSING











Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: .5 mm [.02 in]

Number of Positions: 32

Centerline (Pitch): 1.8 mm [ .071 in ]

Hybrid Connector: No

All MQS, CONNECTOR HOUSING (557)

## Features

### Product Type Features

Cable Exit Angle

Primary Product Color

**Body Material** 

Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Hybrid Connector	No
Primary Locking Feature	Locking Lance
Connector & Contact Terminates To	Flexible Printed Circuit (FPC)
Configuration Features	
Blank Cavity Position	32
Number of Positions	32
Number of Rows	2
Body Features	

180°

Blue

PBT GF



Connector Code	Z
Contact Features	
Contact Size	.5mm
Contact Type	Receptacle
Mating Tab Width	.5 mm[.02 in]
Contact Current Rating (Max)	1 A
Mechanical Attachment	
Terminal Position Assurance	Yes
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	1.8 mm[.071 in]
Dimensions	
Product Width	14.8 mm[.583 in]
Product Length	35 mm[1.38 in]
Product Height	17.8 mm[.7 in]
Row-to-Row Spacing	1.5 mm[.059 in]
Usage Conditions	
Operating Temperature (Max)	65 °C, 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C[149 °F][158 °F][167 °F][176 °F] [185 °F][194 °F][212 °F][221 °F]
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
Agency/Standard	LV214
Packaging Features	
Packaging Quantity	1000
Packaging Method	Bag
Other	
Connector Position Assurance Capable	No



## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





Also in the Series | Nano MQS





Automotive Housings(53)



Automotive Terminals(7)



Insertion & Extraction Tools(6)



PCB Headers & Receptacles(28)

## Customers Also Bought







TE Part #2329120-1 12POS,0.63X0.63,TAB HSG,UNSLD, COD 1







## **Documents**

## **Product Drawings**

32POS,NANOMQS,REC HSG,UNSLD,COD NEUT

English

## **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2303088-1\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2303088-1\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2303088-1\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Housing for Female Terminals, 32 Position, .071 in [1.8 mm] Centerline, Blue, Flexible Printed Circuit (FPC), Signal, Nano MQS



**Product Specifications** 

**Application Specification** 

English

Product Environmental Compliance

**Product Compliance** 

English

**Product Compliance** 

English