


**Specifications**  
 Current Rating: 3Amp  
 Insulation Resistance: 1000MΩ Min.  
 Dielectric Withstanding: 600VAC  
 Contact Resistance: 20mΩ Max.  
 Operating Temperature: -40°C to +105°C  
**Materials**  
 Contact Material: Brass  
 Insulator Material: Polyester, UL 94V-0  
 Nylon 6T  
 Contact plating: Gold Flash

All materials must be GP materials

NUMBER OF POSITIONS	Dimensions	
	A	B
10	20.32	12.70
14	25.40	17.78
16	27.94	20.32
20	33.02	25.40
26	40.64	33.02
30	45.72	38.10
34	50.80	43.18
40	56.42	50.80
50	71.12	63.50
60	83.82	76.20
64	88.90	81.28

# Cnc Tech, LLC

Industrial Cable and Connector Technology

<b>DESIGN</b>	<i>lumayc</i>	<b>PART NO.</b>	3020-XX-0300-00	
<b>DATE</b>	2011.12.05	<b>REV</b>	A	
<b>CHECKED</b>		<b>UNIT</b>	mm	
<b>SIZE</b>	A4	<b>SIZE</b>		
			<b>DIMENSIONAL SPECIFIED TOLERANCES</b>	ANG ±5° 0 ±0.3 .0 ±0.15 .00 ±0.10