

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** 0003091125  
**Status:** Active  
**Overview:** Standard .093" Pin and Socket Connectors  
**Description:** 2.36mm Diameter Standard .093" Pin and Socket Receptacle Housing, 12 Circuits, 3 Rows, Natural

**Documents:**

|                                                      |                                                               |
|------------------------------------------------------|---------------------------------------------------------------|
| <a href="#">3D Model</a>                             | <a href="#">Product Specification PS-43660-9999-001 (PDF)</a> |
| <a href="#">Drawing (PDF)</a>                        | <a href="#">Packaging Specification PK-1360-001 (PDF)</a>     |
| <a href="#">3D Model (PDF)</a>                       | <a href="#">RoHS Certificate of Compliance (PDF)</a>          |
| <a href="#">Product Specification PS-02-09 (PDF)</a> |                                                               |

**Agency Certification**

|     |         |
|-----|---------|
| CSA | LR19980 |
| UL  | E29179  |

**General**

|                |                                                                               |
|----------------|-------------------------------------------------------------------------------|
| Product Family | Crimp Housings                                                                |
| Series         | 1360                                                                          |
| Application    | Power, Wire-to-Wire                                                           |
| Comments       | 12.5A max. can be achieved when housing is used with 42477 or 42478 terminals |
| Overview       | <a href="#">Standard .093" Pin and Socket Connectors</a>                      |
| Product Name   | Standard .093"                                                                |
| UPC            | 800753618831                                                                  |

**Physical**

|                               |                |
|-------------------------------|----------------|
| Circuits (maximum)            | 12             |
| Color - Resin                 | Natural        |
| Flammability                  | 94V-2          |
| Gender                        | Receptacle     |
| Glow-Wire Capable             | No             |
| Material - Resin              | Nylon          |
| Net Weight                    | 1.223/g        |
| Number of Rows                | 3              |
| Packaging Type                | Bag            |
| Panel Mount                   | Yes            |
| Pitch - Mating Interface      | 5.03mm         |
| Pitch - Termination Interface | 5.03mm         |
| Stackable                     | No             |
| Temperature Range - Operating | -40° to +105°C |

**Solder Process Data**


|                             |     |
|-----------------------------|-----|
| Lead-freeProcess Capability | N/A |
|-----------------------------|-----|

**Material Info**

|                    |         |
|--------------------|---------|
| Engineering Number | 1360-R2 |
|--------------------|---------|

**Reference - Drawing Numbers**

|                         |                             |
|-------------------------|-----------------------------|
| Packaging Specification | PK-1360-001                 |
| Product Specification   | PS-02-09, PS-43660-9999-001 |
| Sales Drawing           | SD-1360-X                   |



Series image - Reference only

**EU ELV**

Not Relevant

**EU RoHS**

Compliant

**China RoHS**

**REACH SVHC**

Not Contained Per -  
D(2020)4578-DC (25  
June 2020)

**Halogen-Free**

**Status**

Low-Halogen

For more information, please visit [Contact US](#)

|                 |               |
|-----------------|---------------|
| China ROHS      | Green Image   |
| ELV             | Not Relevant  |
| RoHS Phthalates | Not Contained |

**Search Parts in this Series**

1360 Series

**Mates With**

03092121 , 3099

**Use With**

1189 Crimp Terminals, 1190 Crimp Terminals, 1376 Male PC Tail Terminals, 1377 Female PC Tail Terminals, 1380 Male Crimp Terminals, 1381 Female Crimp Terminals, 1433 Crimp Terminals, 1434 Male Crimp Terminals, 1973