Part Number: 0342503018
Status: Active
Overview: MX150™ Sealed and Unsealed Connector System
Description: MX150™ Cable Sealed Female Connector, Single Row, 3 Circuits, Polarization A, without Connector Position Assurance, Gray

Series image - Reference only

Documents:
Drawing (PDF)
Product Specification PS-34250-000 (PDF)
Application Specification AS-34250-100 (PDF)
RoHS Certificate of Compliance (PDF)

General	
Product Family	Crimp Housings
Series	34250
Application	Power, Wire-to-Wire
Comments	No Connector Position Assurance (CPA)
More Detailed Tech Information	http://uscar.org/guest/teams/10/Electrical-Wiring-Component-Applications-Partnership
Overview	MX150™ Sealed and Unsealed Connector System
Product Name	MX150™
UPC	884982021921
Physical	
Circuits (maximum)	3
Circuits Detail	3
Gender	Female
Glow-Wire Compliant	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Resin	Modified Polystyrene Alloy
Net Weight	7.327/g
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	4.50mm
Pitch - Termination Interface	4.50mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40°C to +125°C
Electrical	
Current - Maximum per Contact	15.0A
Solder Process Data	
Lead-freeProcess Capability	N/A
Material Info	
Reference - Drawing Numbers	
Application Specification	AS-34250-100
Product Specification	PS-34250-000
Sales Drawing	SD-34250-002

EU ELV
Compliant

EU RoHS
Compliant

China RoHS

REACH SVHC
No -ED/108/2014 (17 Dec 2014)

Halogen-Free Status
Not Relevant

Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the Contact Us section for any non-product compliance questions.

China ROHS	Not Relevant
ELV	Compliant

Search Parts in this Series
34250 Series

Use With
34083 Tin (Sn) Cable Seal Female Terminal, 34081 Gold (Au) Cable Seal Female Terminal