



NOTES

1. MATERIAL: COPPER ALLOY, $t=0.25\text{mm}$
2. FINISH: PRE-TIN PLATED
3. RECOMMENDED LENGTH OF WIRE STRIP: 5.0-5.6

NO.	ENG. NO.	TYPE	DESCRIPTION	CABLE SIZE(mm ²) AVS. AVSS	DIMENSION			
					W1	H1	W2	H2
1	35407-6702	S	.090 SEALED FEMALE TER'L	0.3 - 0.5	2.5	2.2	5.1	4.2
2	35407-6802	M	.090 SEALED FEMALE TER'L	0.85-1.25	2.6	3.0	5.2	4.7
3	35407-6902	L	.090 SEALED FEMALE TER'L	2.0	4.0	3.5	5.2	4.7

CHANGED OF ISOMETRIC EC NO: KOR2008-0108 DRWNEOKIM 2007/12/28 CHKD:BCYOON 2008/01/02 APPR: YUNSIKKIM 2008/01/02	QUALITY SYMBOLS	DESCRIPTION REV
	$\blacktriangledown = 0$ $\triangleleft = 0$	
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	
	SIZE A3	

GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION															
<table border="1"> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> <tr> <td>4 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>3 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>2 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>1 PLACE</td> <td>± 0.25</td> <td>± ---</td> </tr> </table>		mm	INCH	4 PLACES	± ---	± ---	3 PLACES	± ---	± ---	2 PLACES	± ---	± ---	1 PLACE	± 0.25	± ---	MM ONLY	5:1	METRIC	
	mm	INCH																	
4 PLACES	± ---	± ---																	
3 PLACES	± ---	± ---																	
2 PLACES	± ---	± ---																	
1 PLACE	± 0.25	± ---																	
DRAWN BY: BCYOON		DATE: 1998/04/10		TITLE: .090 SEALED FEMALE TER'L															
CHECKED BY: BKCHOI		DATE: 1998/04/10		MOLEX INCORPORATED															
APPROVED BY: CWLEE		DATE: 1998/04/10																	
MATERIAL NO.		DOCUMENT NO.		SHEET NO.															
SEE TABLE		SD-35407-001		1 OF 1															