


110 SERIES RECEPTACLES STRAIGHT INSULATION SUPPORT

FASTON Receptacles
Stock Thickness: .010




Wire Range AWG	Fits Tab ²	Fits Type Tab	Insulation Diameter	Dimensions			Material and Finish	Terminal Part No.	UL	M	CS	Quick-Change Applicator No. ■
				L	E	T						
30-28	2	.020	.040-.040	.560	.250	.025	Pre-Tin Brass	62585-1	—	—	—	466361-1
				.635	.250	.025	Pre-Tin Brass	63634-1	X ¹	—	X	687896-2
24-22	1	.016	.040-.060	.635	.250	.025	Pre-Tin Brass	42067-1	X ¹	—	—	687896-2
				.510	.125	.025	Pre-Tin Brass	60089-2	X	—	X	466020-2
22-20	2	.020	.060-.100	.635	.250	.025	Pre-Tin Brass	42236-1	X	—	X	687892-3
				.635	.250	.025	Brass	42068-0	X	—	X	687892-3
	1	.020	.060-.100	.635	.250	.025	Pre-Tin Brass	42068-1	X	—	X	687892-3
				.635	.250	.025	Pre-Tin Brass	60415-1	—	—	—	687892-3
	1	.016	.060-.100	.635	.250	.025	Pre-Tin Brass	60118-1	—	—	—	687892-3
				.635	.250	.025	Pre-Tin Brass	60197-1	X	—	X	687892-3
22-18	3	.032	.060-.100	.635	.250	.025	Pre-Tin Brass	60577-1	—	—	X	687892-3
				.635	.250	.020	Pre-Tin Brass	60729-1	—	—	X	687967-3
	2	.025	.120-.140	.635	.250	.025	Pre-Tin Brass	63568-1	—	—	—	687967-3
				.635	.250	.020	Pre-Tin Brass	61158-1	—	—	—	687967-3
	1	.025	.120-.140	.635	.250	.020	Pre-Tin Brass	62094-1	X	—	X	466178-2
				.635	.250	.020	Brass	62094-2	X	—	X	466178-2
	—	.016	.090-.130	.625	.250	.025	Pre-Tin Brass	62523-1 ³	—	—	—	466767-1
				.635	.250	.020	Pre-Tin Brass	63954-1	X	—	X	687967-3
	1	.020	.060-.100	.635	.250	.025	Pre-Tin Brass	61400-1	X	—	X	466060-3
				.635	.250	.025	Pre-Tin Brass	61408-1	X	—	X	466141-2
20-16	1	.032	.120-.140	.635	.250	.020	Pre-Tin Brass	62050-1	X	—	X	466060-3
				.635	.250	.020	Nickel Plated Steel	62050-2	—	—	—	466060-3
	—	.010	.060-.100	.625	.250	.025	Tin Plated Brass	62191-1	X	—	X	466048-2
				.625	.250	.025	Pre-Tin Brass	62968-1	—	—	—	466141-2
	2	.032	.120-.140	.635	.250	.025	Pre-Tin Brass	63703-1	X	—	X	466060-3
				.635	.250	.025	Tin Plated Brass	63092-1	X	—	X	567044-4
18-14	1, 2, 3	.032	.110-.190	.625	.250	.025	Tin Plated Brass	63093-1 ³	X	—	X	466881-4

¹UL listed 22 AWG wire only.

²See page 34.

³.012 stock

Commercial Line
(Receptacle and
Tab Combination)
Tab Thickness: .020
Receptacle Stock
Thickness: .010



Wire Range AWG	Fits Tab	Insulation Diameter	Dimensions		Material and Finish	Terminal Part No.	UL	M	CS	Quick-Change Applicator No. ■	
			L	T							
22-18		.018	.080-.120	.630	.025	Brass	63242-1	X	—	X	466501-2
				.630	.025	Brass	62003-1	X	—	X	466501-2
		.020	.060-.100	.630	.025	Tin Plated Brass	62003-2	X	—	X	466501-2
				.630	.025	Tin Plated Brass	63961-1	X	—	X	466501-2

■ Quick-Change Applicator for AMP-O-ELECTRIC Machine 565435-5.
For AMPOMATOR Machine and other machines not listed, contact AMP Incorporated.