SPLICE

TE Internal #: 42329-1

Splices, 3200 – 3900 CMA Wire Size, Steel, Pigtail Splice / Thru Splice Splice, 0 Serration, Length .15 in [3.81 mm], Reel, Open,

SPLICE

View on TE.com >



Terminals & Splices > Splices











Sealable: No

Wire Size: 3200 – 3900 CMA

Primary Product Material: Steel

Splice Type: Pigtail Splice, Thru Splice

Terminal Material Thickness: .3 mm [.012 in]

Features

Product Type Features

Barrel Style	Standard
Sealable	No
Splice Type	Pigtail Splice, Thru Splice
Serrated	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support
Configuration Features	
Number of Serrations	0
Compatible With Wire & Cable Type	Discrete Wire
Body Features	
Weight per Piece	.089 g

Nickel

Steel

Contact Features

Plating Material

Primary Product Material



Barrel Type	Open
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Wire Size	3200 – 3900 CMA
Terminal Material Thickness	.3 mm[.012 in]
Overall Product Length	3.81 mm[.15 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 - 250 °C[-40 - 482 °F]
Operation/Application	
Heavy Duty	No
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	33000
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 61021-1 SPLICE 18-16 AWG .0126 NPST



TE Part # 42627-4 SPLICE 3232-8282 .0198 NPST



TE Part # 60933-2 SPLICE 2200-2900 .012 TPST



TE Part # 41627-1 SPLICE 4000-10000 .025 ST



TE Part # 61008-1 SPLICE 18-16 AWG .0158 TPST



TE Part # 160659-2 SPLICE 800-2500 .016 NPST



TE Part # 2-2150684-1
OCEAN_2.0_Applicator-E-100F



TE Part # 2-2150684-2 OCEAN_2.0_Applicator-E-100F



TE Part # 2150684-1
OCEAN_2.0_Applicator-E-100F



TE Part # 2150684-2 OCEAN_2.0_Applicator-E-100F



TE Part # 7-2150684-1
OCEAN_2.0_Applicator-E-100F



TE Part # 7-2150684-2
OCEAN_2.0_Applicator-E-100F



TE Part # 7-2150684-7

OCEAN_2.0_SPARE_PART_KIT-100F



Also in the Series | SPLICE









TE Part #63136-1

250 AMVAR TAB 200-860 TPBR



PLUG, 2 CIRCUIT, UNIVERSAL MATE-



SPADE TERMINAL 18-14 AWG TPBR

TE Part #60774-2

Documents

TE Part #1-1703061-2

N-LOK

Product Drawings
SPLICE 1200-2600 .012 NPST

English

CAD Files

3D PDF

3D



Customer View Model

ENG_CVM_CVM_42329-1_J_c-42329-1-j.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_42329-1_J_c-42329-1-j.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_42329-1_J_c-42329-1-j.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Product Environmental Compliance

TE Material Declaration

English