


S P A D E & R I N G


## Spade and Ring Series Uninsulated

**.625 Ring  
12-8 AWG**

STYLE AND DIMENSIONS	STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	.385	None	— —	3000	$\frac{9}{32} \pm \frac{1}{32}$	.040	Brass	3800M 26
							Pre Tinned Brass	3800M 26A


## Spade and Ring Series Uninsulated

**.175 Ring  
Insulation Piercing — 2 Barbs**

STYLE AND DIMENSIONS	STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	0	.075-.125	— —	7000	—	.020	Brass	40041
							Pre Tinned Brass	40042
	2	.075-.125	— —	7000	—	.020	Brass	40045
							Pre Tinned Brass	40046
	3	.075-.125	— —	7000	—	.020	Brass	40057
							Pre Tinned Brass	40058
	4	.075-.125	— —	7000	—	.020	Brass	40061
							Pre Tinned Brass	40062

## Spade and Ring Series Uninsulated

**.240 Ring  
Insulation Piercing — 2 Barbs**

STYLE AND DIMENSIONS	STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	0	.075-.125	— —	6000	—	.020	Brass	2H1-0
							Pre Tinned Brass	2H2-0
	2	.075-.125	— —	6000	—	.020	Brass	2H1-2
							Pre Tinned Brass	2H2-2
	4	.075-.125	— —	6000	—	.020	Brass	2H1-4
							Pre Tinned Brass	2H2-4
6	.075-.125	— —	6000	—	.020	Brass	2H1-6	
						Pre Tinned Brass	2H2-6	