



Terminals & Splices > Crimp Wire Pins, Tabs & Ferrules



Crimp Wire Pin, Tab & Ferrule Terminal Type: **Receptacle**

Pin Diameter: **2.36 mm [.093 in]**

Accepts Wire Insulation Diameter Range: **1.14 – 2.16 mm, 2.16 mm [.045 – .085 in, .085 in]**

Wire Size: **.2 – .8 mm²**

Features

Product Type Features

Compatible With Discrete Wire Type	Solid, Stranded
------------------------------------	-----------------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Contact Features

Crimp Wire Pin, Tab & Ferrule Terminal Type	Receptacle
Barrel Type	Open
Terminal Plating Material	Tin
Terminal Orientation	Straight

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Pin Diameter	2.36 mm [.093 in]
Accepts Wire Insulation Diameter Range	1.14 – 2.16 mm, 2.16 mm [.045 – .085 in][.085 in]
Wire Size	404 – 1624 CMA



Barrel Inside Diameter	1.01 mm, 1.65 mm [.04 in][.065 in]
Terminal Material Thickness	.3 mm [.012 in]
Overall Product Length	14.23 mm [.56 in]

Usage Conditions

Insulation Option	Uninsulated
-------------------	-------------

Operation/Application

Heavy Duty	No
------------	----

Packaging Features

Packaging Quantity	20000
Packaging Method	Reel

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts

TE Part # 140712-2
PIN .155 DIA REC 18-14 AWG TPBR

TE Part # 60885-2
PIN .055 REC 24-20 AWG TPPHBZ

TE Part # 60440-1
PIN 093 RECEPTACLE 22-18 AWG BR

TE Part # 2-2150541-1
OC-PA-E-FM-070F0900-001-0033

TE Part # 2-2150541-2
OC-PA-E-FA-070F0900-001-0033

TE Part # 2150541-1
OC-AT-E-FM-070F0900-001-0033

TE Part # 2150541-2
OC-AT-E-FA-070F0900-001-0033

TE Part # 7-2150541-7
OC-070F0900-CRIMPTOOLINGKIT

TE Part # 60884-3
PIN REC 22-18 AWG .0126 X .380 TPBR

Customers Also Bought

TE Part # 641967-1
04P UMNL PIN HDR ASSY POL NATL

TE Part # 62050-2
110 FASTON REC 20-16 AWG NPST

TE Part # 42640-2
250 FASTON REC 22-18 AWG TPBR

TE Part # 62814-2
250 FASTON FLAG REC 22-18 AWG TPBR

TE Part # 42692-2
250 FASTON REC 18-14 AWG TPBR

TE Part # 170183-2
250 FASTON,REC.,22-18 AWG,TPBR

TE Part # 607381P046
SCT-NO.2-E5-0-STK

TE Part # 3-640108-1
AMP-IN, MINI 26-22 008PTLPHBZ



Documents

Product Drawings

[PIN .093 RECEPTACLE 24-18 AWG TPBR](#)

English

CAD Files

Customer View Model

[ENG_CVM_CVM_42827-2_AC.2d_dxf.zip](#)

English

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_42827-2_AC.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_42827-2_AC.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English

[Pin Receptacle Contact With Closed Seam](#)

English

Product Environmental Compliance

[MD_42827-2_1003201635_dmtec](#)

English

[MD_42827-2_1003201635_dmtec](#)

English