Econoseal J - Mark II

TE Internal #: 368536-1

Wire-to-Wire, 12 Position, .189 in [4.8 mm] Centerline, Sealable,

Black, Cable Mount (Free-Hanging), Econoseal J - Mark II

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > ECONOSEAL, CONNECTOR HOUSING











Connector System: Wire-to-Wire

Number of Positions: 12

Centerline (Pitch): 4.8 mm [.189 in]

Sealable: Yes

Hybrid Connector: No

All ECONOSEAL, CONNECTOR HOUSING (90)

Features

Product Type Features

Connector & Housing Shape	Rectangular
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No

Configuration Features

Number of Positions	12	
Number of Rows	6	

Body Features

Contact Features	
Primary Product Color	Black
Body Material	PBT GF



Mounting Feature	Without
Terminal Position Assurance	No
Mating Alignment Type	Polarization Slot
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	4.8 mm[.189 in]
Dimensions	
Product Width	33.2 mm[1.307 in]
Product Length	40.6 mm[1.598 in]
Product Height	27.6 mm[1.086 in]
Row-to-Row Spacing	5.6 mm[.22 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C[158 °F][167 °F][176 °F][185 °F][194 °F] [212 °F][221 °F]
Operating Temperature Range	-30 - 105 °C[-22 - 221 °F]
Industry Standards	
UL Flammability Rating	UL 94V-2
Packaging Features	
Packaging Quantity	50
Other	
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold:



$NI \rightarrow$	\/_+	Reviewed
IMOI	$Y \cap T$	Keviewed

Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts






Also in the Series | Econoseal J - Mark II









Customers Also Bought















Documents

Product Drawings

E-S MK-2(+) 12P PLUG ASS'Y

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_368536-1_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_368536-1_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_368536-1_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Econoseal Connector Series

English

Product Specifications

AMP-ECONOSEAL-J MARK II+ CONNECTOR

English

Product Specification

English

Wire-to-Wire, 12 Position, .189 in [4.8 mm] Centerline, Sealable, Black, Cable Mount (Free-Hanging), Econoseal J - Mark II

