

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0039000219](#)
Status: **Active**
Overview: [Mini-Fit Jr. Power Connectors](#)
Description: [Mini-Fit Male Crimp Terminal, Phosphor Bronze, Gold \(Au\), 18-24 AWG, Reel](#)

Documents:

Drawing (PDF)	Packaging Specification 55580001-PK-000 (PDF)
Product Specification 55560008-TS-000 (PDF)	Test Summary 55560010-TS-000 (PDF)
Product Specification PS-5556-001-001 (PDF)	Test Summary TS-5556-002-001 (PDF)
Product Specification PS-5556-002-001 (PDF)	RoHS Certificate of Compliance (PDF)
Application Specification 55560001-AS-000 (PDF)	



General

Product Family	Crimp Terminals
Series	5558
Application	Power, Wire-to-Wire
Crimp Quality Equipment	Yes
Overview	Mini-Fit Jr. Power Connectors
Packaging Alternative	39000220 (Loose)
Product Name	Mini-Fit
UPC	800754396349

Physical

Durability (mating cycles max)	30
Gender	Male
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Net Weight	126.914/mg
Packaging Type	Reel
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	1.30-3.10mm
Wire Size AWG	18, 20, 22, 24
Wire Size mm ²	N/A

Electrical

Current - Maximum per Contact	9.0A
Voltage - Maximum	600V

Solder Process Data

Lead-freeProcess Capability	N/A
-----------------------------	-----

Material Info

Engineering Number	5558PBGS
--------------------	----------

Reference - Drawing Numbers

Application Specification	55560001-AS-000
Packaging Specification	55580001-PK-000
Product Specification	55560008-TS-000 , PS-5556-001-001 , PS-5556-002-001
Sales Drawing	SD-5558-002-001
Test Summary	55560010-TS-000 , TS-5556-002-001

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2020)4578-DC (25
June 2020)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[5558 Series](#)

Use With

Mini-Fit Jr. Plug Housing [5559](#)
Mini-Fit
BMI Plug Housing [42475](#)

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description

Product #

Extraction Tool	11030044
FineAdjust Applicator	2037026300
for Mini-Fit Double Crimp Applications Using Two 22 AWG Wires	
Hand Crimp Tool	638190901
for Mini-Fit Jr. Male and Female Crimp	

Terminals, 18-24
 AWG
 FineAdjust Applicator [639015600](#)
 for Insulation OD
 1.90-2.30mm - 18-24
 AWG
 FineAdjust Applicator [639023900](#)
 for Insulation OD
 1.40-1.70mm - 18-24
 AWG
 FineAdjust Applicator [639024800](#)
 for Insulation OD
 2.50-2.95mm
 Optimized for 18
 AWG Only
 FineAdjust Applicator [639024900](#)
 for Insulation OD
 2.30-2.60mm - 18-24
 AWG
 FineAdjust Applicator [639047800](#)
 for Insulation OD
 2.50-2.95mm, 18-24
 AWG
 FineAdjust Applicator [639048000](#)
 for Insulation OD
 1.65-2.05mm, 18-24
 AWG
 T2 Terminator [639115600](#)
 for insulation OD
 1.90-2.30mm - 18-24
 AWG
 T2 Terminator [639123900](#)
 for insulation OD
 1.40-1.70mm - 18-24
 AWG
 T2 Terminator [639124800](#)
 for insulation OD
 2.50-2.95mm
 optimized for 18
 AWG only
 T2 Terminator [639124900](#)
 for insulation OD
 2.30-2.60mm - 18-24
 AWG
 T2 Terminator [639147800](#)
 for Mini-Fit Crimp
 Terminals, 18-24
 AWG with Large
 Insulation ODs
 T2 Terminator [639148000](#)
 for Mini-Fit Crimp
 Terminals, 18-24
 AWG with Smaller
 Insulation ODs

This document was generated on 07/17/2020

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION