

TE Internal #: 440054-2

PCB Mount Header, Vertical, Wire-to-Board, 2 Position, .079 in [2 mm] Centerline, Fully Shrouded, Tin, Through Hole - Solder, Signal,

Natural


View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > AMP HPI 2.0MM HEADERS











Connector System: Wire-to-Board

Number of Positions: 2

Number of Rows: 1

Centerline (Pitch): 2 mm [.079 in]
PCB Mount Orientation: Vertical

All AMP HPI 2.0MM HEADERS (212)

# Features

# **Product Type Features**

| Connector System                  | Wire-to-Board         |
|-----------------------------------|-----------------------|
| Header Type                       | Fully Shrouded        |
| Sealable                          | No                    |
| Connector & Contact Terminates To | Printed Circuit Board |
| PCB Connector Assembly Type       | PCB Mount Header      |
| Configuration Features            |                       |

| Number of Positions   | 2        |
|-----------------------|----------|
| Number of Rows        | 1        |
| PCB Mount Orientation | Vertical |

## **Electrical Characteristics**

| Operating Voltage | 250 VAC |
|-------------------|---------|
| Operating voitage | 230 VAC |

# **Body Features**

| Primary Product Color Natural |
|-------------------------------|
|-------------------------------|



### **Contact Features**

| Contact Mating Area Length                           | 3.35 mm[.131 in] |
|--|------------------|
| Mating Square Post Dimension                         | .5 mm[.02 in]    |
| Contact Mating Area Plating Material Thickness       | 2.032 µm[80 µin] |
| PCB Contact Termination Area Plating Material Finish | Bright           |
| Contact Shape & Form                                 | Square           |
| Contact Mating Area Plating Material Finish          | Bright           |
| PCB Contact Termination Area Plating Material        | Tin              |
| Contact Base Material                                | Brass            |
| Contact Mating Area Plating Material                 | Tin              |
| Contact Type   | Pin              |
| Contact Current Rating (Max)                         | 3 A              |

## **Termination Features**

| Square Termination Post & Tail Dimension    | .5 mm[.02 in]         |
|---|-----------------------|
| Terminations per Post (Max)                 | 3                     |
| Termination Post & Tail Length              | 3.4 mm[.134 in]       |
| Termination Method to Printed Circuit Board | Through Hole - Solder |

## Mechanical Attachment

| Mating Alignment Type    | Polarization |
|--------------------------|--------------|
| Mating Retention         | Without      |
| PCB Mount Retention Type | Kinked Tines |
| Connector Mounting Type  | Board Mount  |
| Mating Alignment         | With         |
| PCB Mount Alignment      | Without      |
| PCB Mount Retention      | With         |

# Housing Features

| Housing Material   | Nylon 66 GF   |
|--------------------|---------------|
| Centerline (Pitch) | 2 mm[.079 in] |

## **Dimensions**

| Connector Length | 6 mm[.236 in]    |
|------------------|------------------|
| Connector Height | 6.05 mm[.238 in] |
| Connector Width  | 4.7 mm[.185 in]  |



| PCB Thickness (Recommended) | 1 – 1.6 mm[.039 – .063 in] |
|-----------------------------|----------------------------|
| Usage Conditions            |                            |
| Operating Temperature Range | -25 – 85 °C[-13 – 185 °F]  |
| Operation/Application       |                            |
| Circuit Application         | Signal                     |
| Industry Standards          |                            |
| UL Flammability Rating      | UL 94V-0                   |
| Packaging Features          |                            |
| Packaging Quantity          | 300                        |
|                             |                            |

Bag

## **Product Compliance**

Packaging Type

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per<br>homogenous material. Also BFR/CFR/PVC<br>Free                                 |
| Solder Process Capability                     | Wave solder capable to 240°C  |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





# Customers Also Bought











## **Documents**

## **Product Drawings**

2.0MM,HDR,2POS,VERTICAL

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_440054-2\_F4.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_440054-2\_F4.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_440054-2\_F4.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use



# Datasheets & Catalog Pages

HPI Connectors QRG

English

## **Product Specifications**

**Application Specification** 

English

# Product Environmental Compliance

MD\_440054-2\_0607201896\_dmtec

English

MD\_440054-2\_0607201896\_dmtec

English

# Agency Approvals

**UL Report** 

English