

42437-2 ✓ ACTIVE

FASTON | FASTON 250


TE Internal #: 42437-2

Quick Disconnects, Receptacle, 14 – 10 AWG Wire Size, 2.08 – 5.26 mm² Wire Size, Mating Tab Width .25 in [6.35 mm], Straight, Brass, FASTON 250

[View on TE.com >](#)



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **2.08 – 5.26 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Terminates To	Wire & Cable
Wire/Cable Type	Regular Wire
Wire Stop	No
Insertion Force	Low
Sealable	No

Configuration Features

Connection Capacity	Single
---------------------	--------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp



Barrel Type	Open
-------------	------

Mechanical Attachment

Mating Retention Type	Dimple
Wire Insulation Support	With

Dimensions

Accepts Wire Insulation Diameter Range	3.81 – 5.08 mm [.15 – .2 in]
Receptacle Terminal Stock Thickness	.43 mm [.017 in]
Overall Length	19.56 mm [.77 in]
Wire Size	2.08 – 5.26 mm ²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C [-40 – 230 °F]

Industry Standards

CSA Certified	Yes
UL Rating	Listed

Packaging Features

Packaging Quantity	8000
Packaging Method	Strip/Reel

Other

Line	Premier
------	---------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



KIT
REPRESENTATION ONLY

TE Part # 7-2150237-7
OCEAN_2.0_SPARE_PART_KIT-130F2100



TE Part # 5-160521-2
375 FASTON REC 12-10 AWG TPBR



TE Part # 2-2150237-1
OCEAN_2.0_APPLICATOR-E-130F2100



TE Part # 2-2150237-2
OCEAN_2.0_APPLICATOR-E-130F2100



TE Part # 2150237-1
OCEAN_2.0_APPLICATOR-E-130F2100



TE Part # 2150237-2
OCEAN_2.0_APPLICATOR-E-130F2100




TE Part # 2376595-2
250 FASTON PCB TAB TPBR




TE Part # 2376591-3
250 FASTON PCB TAB TPBR LP


Also in the Series | FASTON 250



Compression Connectors(4)



Crimp Terminal Housings(143)



Insertion & Extraction Tools(6)



Magnet Wire Terminals(1)



PCB Terminals(144)





Quick Disconnects(456)



Splices(4)

Customers Also Bought

TE Part #173090-2
.070 ECONOSEAL PLUG ASSY 2PTE Part #52922-1
TERMINAL,PIDG SPR SPD 26-22 4TE Part #2007304-5
HEAT SINK CLIP QSFP28TE Part #3-643819-7
07P MTA156 CONN ASSY 22AWG REDTE Part #2007304-1
Heat sink Clip QSFPTE Part #5120658-2
Z-PACK HS3 HDR ASY 10R 100PTE Part #1-292138-8
CT DOUBLE ROW ASSY H 18P HDR NTE Part #1-480710-2
15P UMNL PLUG HSG REDTE Part #583853-3
TWIN LEAF TERM. STRIP CSTLTE Part #1-1393127-1
PRD-11AG0-24=PRD

Documents

Product Drawings

[250 FASTON REC 14-10 AWG TPBR](#)

English

CAD Files

[Customer View Model](#)

[ENG_CVM_CVM_42437-2_AU.2d_dxf.zip](#)

English

[3D PDF](#)



3D

Customer View Model

[ENG_CVM_CVM_42437-2_AU.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_42437-2_AU.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[82004 FASTON Terminals \(Insulated and Uninsulated\) Catalog - FASTON Receptacles Section](#)

English

Product Specifications

[Application Specification](#)

English

[Application Specification](#)

English

[Wire Preparation And Crimp Inspection Guide](#)

English

Product Environmental Compliance

[Product Compliance](#)

English

[Product Compliance](#)

English