

5-104549-6 ✓ ACTIVE

AMPMODU | AMPMODU System 50


TE Internal #: 5-104549-6

PCB Mount Header, Vertical, Board-to-Board / Wire-to-Board, 40
Position, .05 in [1.27 mm] Centerline, Fully Shrouded, Gold,
AMPMODU System 50

[View on TE.com >](#)



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Header**

PCB Mount Orientation: **Vertical**

Connector System: **Board-to-Board, Wire-to-Board**

Number of Positions: **40**

Number of Rows: **2**

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Header
Connector System	Board-to-Board, Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Vertical
Number of Positions	40
Number of Rows	2

Electrical Characteristics

Operating Voltage	30 VAC
-------------------	--------

Body Features

Connector Profile	Standard
Primary Product Color	Black

Contact Features

	150 – 250 μ m
PCB Contact Termination Area Plating Material Finish	Matte



Contact Mating Area Plating Material Finish	Bright
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material	Gold
Contact Type	Pin
Contact Current Rating (Max)	1 A

Termination Features

Termination Post & Tail Length	2.54 mm[.1 in]
Termination Method to Printed Circuit Board	Surface Mount

Mechanical Attachment

Mating Retention	With
Panel Mount Feature	Without
PCB Mount Retention Type	Hold-Down Post
Mating Alignment	With
Mating Alignment Type	Latched
PCB Mount Retention	With
PCB Mount Alignment	With
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	1.27 mm[.05 in]
Housing Material	Thermoplastic

Dimensions

Row-to-Row Spacing	2.54 mm[.1 in]
PCB Thickness (Recommended)	1.57 mm

Usage Conditions

Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Solder Process Feature	Board Standoff
Circuit Application	Power & Signal

Industry Standards

Approved Standards	CSA LR7189, UL E28476
--------------------	-----------------------



UL Flammability Rating

UL 94V-0

Packaging Features

Packaging Quantity

16

Packaging Type

Box, Tube

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU

Compliant

EU ELV Directive 2000/53/EC

Compliant

China RoHS 2 Directive MIIT Order No 32, 2016

No Restricted Materials Above Threshold

EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JUNE 2022 (224)
 Candidate List Declared Against: JAN 2022 (223)
 SVHC > Threshold:
 Not Yet Reviewed

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 5-104078-2
40 SYSTEM 50 RCPT ASSY DRST SN



TE Part # 2-111196-0
40 RCPT SYSTEM 50, LEAD FREE



TE Part # 5-104550-5
40 SYS50 SURFMNT DRST RCPT SN



TE Part # 5-147377-4
40 SYS50 SMT HDR DR SHD SN



TE Part # CAT-F439-R2435127
FFC Receptacle Housing: 1.27mm



TE Part # 104549-4
26 SYS50 SURFMNT HDR DRST SHRD



TE Part # 1571480-1
40 SYS50 SURFMNT HDR DRST SHRD



TE Part # 5-147378-4
40 SYS50 SMT RCP DR SHD SN

Also in the Series | **AMPMODU System 50**



PCB Headers & Receptacles(1014)

Customers Also Bought



TE Part #2-644803-5
05P MTA100 SHRD HDR ASST RA FL



TE Part #5745191-1
50 RCPT SP/MS STD



TE Part #5-103167-2
10 MODII HDR DRRA SHRD LF



TE Part #5-104549-3
24 SYS50 S/M HDR DRST SHRDSN



TE Part #7-1676481-9
CPF 0603 13K 0.1% 25PPM 1K RL



TE Part #5-2176091-4
RP 2A 0.25W 210R 0.1% 25PPM 1K RL



TE Part #5747193-2
50 RCPT RA/MS STD (SL)



TE Part #2-1474644-7
FSN-21A-4



Documents

Product Drawings

[40 SYS50 S/M HDR DRST SHRDSN](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_5-104549-6_W.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_5-104549-6_W.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_5-104549-6_W.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[AMPMODU_INTERCONNECTION_SYSTEM_SECTION3AND4](#)

English

[Fine Pitch Stacking Connectors - 1.27mm AMPMODU System 50 Connectors](#)

English

Product Specifications

[Application Specification](#)

English

Product Environmental Compliance

[MD_5-104549-6_032620181014_dmtec](#)

English

[MD_5-104549-6_032620181014_dmtec](#)

English