



|                                                |                                   |
|------------------------------------------------|-----------------------------------|
| Surface Mount Compatible (SMC)                 | Yes                               |
| Temperature Range - Operating                  | -40° to +105°C                    |
| Termination Interface: Style                   | Through Hole                      |
| <b>Electrical</b>                              |                                   |
| Current - Maximum per Contact                  | 13.0A                             |
| Voltage - Maximum                              | 600V AC (RMS)/DC                  |
| <b>Solder Process Data</b>                     |                                   |
| Duration at Max. Process Temperature (seconds) | 030                               |
| Lead-freeProcess Capability                    | SMC&WAVE                          |
| Max. Cycles at Max. Process Temperature        | 003                               |
| Process Temperature max. C                     | 265                               |
| <b>Material Info</b>                           |                                   |
| <b>Reference - Drawing Numbers</b>             |                                   |
| Packaging Specification                        | PK-46207-001-000                  |
| Product Specification                          | PS-45750-001-001, PS-5556-004-001 |
| Sales Drawing                                  | SD-46207-001-000                  |
| Symbol/Footprint Data                          | SYM-46207-0008                    |

This document was generated on 07/16/2020

PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION