531271-1 ✓ ACTIVE

AMP-LEAF


TE Internal #: 531271-1

Housing, Receptacle, Wire-to-Board, 15 Position, 3.96 mm [.156 in] Centerline, Crimp, 2 Row, Black, Wire & Cable, Signal, Board Mount

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings



Connector Product Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 15

Centerline (Pitch): 3.96 mm [.156 in]

Features

Product Type Features

Connector Product Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Dual Positions	15
Number of Positions	15
Number of Rows	2

Electrical Characteristics

Dielectric Withstanding Voltage (Max)	1800 VAC
Insulation Resistance	5000 ΜΩ

Contact Features

Contact Type	Pin
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	3 A

Termination Features

Termination Method to Wire & Cable	Crimp	
------------------------------------	-------	--

Mechanical Attachment



Strain Relief	Without
PCB Mount Retention	Without
Panel Mount Feature Type	Mounting Ears
Mating Retention	Without
Connector Mounting Type	Board Mount
Housing Features	
Housing Entry Configuration	Both Ends Closed
Housing Material	Phenolic - GF
Centerline (Pitch)	3.96 mm[.156 in]
Housing Color	Black
Dimensions	
	.7 in
PCB Thickness (Recommended)	1.4 – 1.78 mm[.055 – .07 in]
Wire Size	.518 mm²
Row-to-Row Spacing	4.14 mm[.163 in]
Row-to-Row Spacing Usage Conditions	4.14 mm[.163 in]
	4.14 mm[.163 in] $-55 - 105 °C[-67 - 221 °F]$
Usage Conditions	
Usage Conditions Operating Temperature Range	
Usage Conditions Operating Temperature Range Operation/Application	-55 – 105 °C[-67 – 221 °F]
Usage Conditions Operating Temperature Range Operation/Application Circuit Application	-55 – 105 °C[-67 – 221 °F]
Usage Conditions Operating Temperature Range Operation/Application Circuit Application Packaging Features	-55 – 105 °C[-67 – 221 °F] Signal
Usage Conditions Operating Temperature Range Operation/Application Circuit Application Packaging Features Packaging Quantity	-55 – 105 °C[-67 – 221 °F] Signal

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224)



Candidate List Declared Against: JUNE 2022 (224)

Does not contain REACH SVHC

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought




















Documents

Product Drawings

HSG AMP LEAF 15 POS

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_531271-1_J.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_531271-1_J.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_531271-1_J.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English

Connector, AMP-LEAF, .000030 Gold Plated Contacts, DPH Housing

English

Product Specification

English

Connector, AMP-LEAF, Phenolic or Thermoplastic Housing

English

Product Specification

English

Connector, AMP-LEAF, Tin Plated Contact

English