5177985-6 ACTIVE

Free Height

TE Internal #: 5177985-6

PCB Mount Receptacle, Vertical, Board-to-Board, 140 Position, .031 in [.8 mm] Centerline, Gold, Surface Mount, Signal, Natural, Free

Height

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > Free Height Receptacle Conn: Board-Board, Vertical, 140, 0.8mm



PCB Connector Assembly Type: PCB Mount Receptacle

PCB Mount Orientation: Vertical
Connector System: Board-to-Board

Number of Positions: 140

Centerline (Pitch): .8 mm [.031 in]

All Free Height Receptacle Conn: Board-Board, Vertical, 140, 0.8mm (21)

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Stackable	Yes
PCB Mount Orientation	Vertical
Number of Positions	140
Board-to-Board Configuration	Parallel
Electrical Characteristics	
Dielectric Withstanding Voltage (Max)	500 VAC
Insulation Resistance	2 ΜΩ



Assembly Process Feature Material Steel Primary Product Color Natural Contact Features Contact Layout Inline PCB Contact Termination Area Plating Material Thickness 2 pmr[28,74 pin] Mating Tab Width A mm[016 in] Mating Tab Thickness 2 mm[008 in] PCB Contact Termination Area Plating Material Finish Matte Contact Shape & Form Square Contact Mating Area Plating Material Finish Matte PCB Contact Termination Area Plating Material Entity Material Contact Mating Area Plating Material Contact Base Material Contact Mating Area Plating Material Contact United Material Contact United Space Contact Current Rating (Max) 5 A Termination Features Rectangular Termination Post & Tail Thickness 2 mm[008 in] Rectangular Termination Post & Tail Width 3 mm[012 in] I remination Method to Printed Circuit Board Surface Mount Mechanical Attachment PCB Mount Alignment Type Positioning Bosses I ocating Post Length 5 mm[02 in] Mating Alignment With	Operating Voltage	100 VAC
Primary Product Color Contact Features Contact Layout Inline PCB Contact Termination Area Plating Material Thickness 2 µm/78.74 µin] Mating Tab Width 4 mm(,016 in) Mating Tab Thickness 2 mm(,008 in) PCB Contact Termination Area Plating Material Finish Matte Contact Shape & Form Square Contact Mating Area Plating Material Finish Matte PCB Contact Termination Area Plating Material Tine Contact Mating Area Plating Material Tine Contact Mating Area Plating Material Gold Contact Mating Area Plating Material Gold Contact Mating Area Plating Material Thickness 2 µm/8 µin] Contact Type Socket Contact Current Rating (Max) 5 A Termination Features Rectangular Termination Post & Tail Thickness 2 mm(,008 in) Rectangular Termination Post & Tail Width 3 mm(,012 in) Termination Method to Printed Circuit Roard Surface Mount Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length 5 mm(,02 in) Mating Alignment	Body Features	
Contact Layout Inline PCB Contact Termination Area Plating Material Thickness 2 µm[78.74 µin] Mating Tab Width4 mm[,016 in] Mating Tab Thickness2 mm[,008 in] PCB Contact Termination Area Plating Material Finish Matte Contact Shape & FormSquare Contact Mating Area Plating Material Finish Matte PCB Contact Termination Area Plating Material Finish Matte PCB Contact Termination Area Plating Material Tinish Matte PCB Contact Mating Area Plating Material Tinish Copper Alloy Contact Mating Area Plating Material Gold Contact Mating Area Plating Material Thickness2 µm[8 µin] Contact Type Socket Contact Current Rating (Max)5 A Termination Features Rectangular Termination Post & Tail Thickness	Assembly Process Feature Material	Steel
Contact Layout PCB Contact Termination Area Plating Material Thickness 2 \(\mu \min[78.74 \times \min] \) Mating Tab Wridth A mm[.016 in] Mating Tab Thickness 2 mm[.008 in] PCB Contact Termination Area Plating Material Finish Matte Contact Shape & Form Square Contact Mating Area Plating Material Finish Matte PCB Contact Termination Area Plating Material Tin Contact Base Material Copper Alloy Contact Mating Area Plating Material Gold Contact Mating Area Plating Material Thickness 2 \(\mu \min[8 \times] \min] Contact Type Socket Contact Type Socket Contact Current Rating (Max) Termination Features Rectangular Termination Post & Tail Thickness 2 \(\mu \min[.008 \times] \min] Termination Method to Printed Circuit Board Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length Mating Alignment With	Primary Product Color	Natural
PCB Contact Termination Area Plating Material Thickness 2 µm[78.74 µin] Mating Tab Width 4 mm[.016 in] Mating Tab Thickness 2. mm[.008 in] PCB Contact Termination Area Plating Material Finish Matte Contact Shape & Form Square Contact Mating Area Plating Material Finish Matte PCB Contact Termination Area Plating Material Tin Contact Base Material Copper Alloy Contact Mating Area Plating Material Gold Contact Mating Area Plating Material Thickness 2. µm[8 µin] Contact Type Socket Contact Current Rating (Max) .5 A Termination Features Rectangular Termination Post & Tail Thickness 2. mm[.008 in] Rectangular Termination Post & Tail Width 3 mm[.012 in] Termination Method to Printed Circuit Board Surface Mount Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length 5 mm[.02 in] Mating Alignment With	Contact Features	
Mating Tab Width 4 mm[.016 in] Mating Tab Thickness 2 mm[.008 in] PCB Contact Termination Area Plating Material Finish Matte Contact Shape & Form Square Contact Mating Area Plating Material Finish Matte PCB Contact Termination Area Plating Material Tin Contact Base Material Copper Alloy Contact Mating Area Plating Material Gold Contact Mating Area Plating Material Thickness 2 µm[8 µin] Contact Type Socket Contact Current Rating (Max) 5 A Termination Features Rectangular Termination Post & Tail Thickness 2 mm[.008 in] Rectangular Termination Post & Tail Width 3 mm[.012 in] Termination Method to Printed Circuit Board Surface Mount Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length 5 mm[.02 in] Mating Alignment With	Contact Layout	Inline
Mating Tab Thickness 2 mm[.008 in] PCB Contact Termination Area Plating Material Finish Matte Contact Shape & Form Square Contact Mating Area Plating Material Finish Matte PCB Contact Termination Area Plating Material Tin Contact Base Material Tin Contact Base Material Copper Alloy Contact Mating Area Plating Material Gold Contact Mating Area Plating Material Thickness 2 µm[8 µin] Contact Type Socket Contact Current Rating (Max) 5 A Termination Features Rectangular Termination Post & Tail Thickness 2 mm[.008 in] Rectangular Termination Post & Tail Width 3 mm[.012 in] Termination Method to Printed Circuit Board Surface Mount Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length 5 mm[.02 in] Mating Alignment With	PCB Contact Termination Area Plating Material Thickness	2 μm[78.74 μin]
PCB Contact Termination Area Plating Material Finish Contact Shape & Form Square Contact Mating Area Plating Material Finish Matte PCB Contact Termination Area Plating Material Contact Base Material Copper Alloy Contact Mating Area Plating Material Contact Mating Area Plating Material Contact Mating Area Plating Material Thickness 2 µm[8 µin] Contact Type Socket Contact Current Rating (Max) 5 A Termination Features Rectangular Termination Post & Tail Thickness 2 mm[.008 in] Rectangular Termination Post & Tail Width 3 mm[.012 in] Termination Method to Printed Circuit Board Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length Mating Alignment With	Mating Tab Width	.4 mm[.016 in]
Contact Shape & Form Contact Mating Area Plating Material Finish PCB Contact Termination Area Plating Material Tin Contact Base Material Copper Alloy Contact Mating Area Plating Material Gold Contact Mating Area Plating Material Contact Mating Area Plating Material Thickness .2 µm[8 µin] Contact Type Socket Contact Current Rating (Max) .5 A Termination Features Rectangular Termination Post & Tail Thickness Rectangular Termination Post & Tail Width .3 mm[.012 in] Termination Method to Printed Circuit Board Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length Mating Alignment With	Mating Tab Thickness	.2 mm[.008 in]
Contact Mating Area Plating Material Finish PCB Contact Termination Area Plating Material Contact Base Material Copper Alloy Contact Mating Area Plating Material Contact Mating Area Plating Material Contact Mating Area Plating Material Thickness 2 µm[8 µin] Contact Type Socket Contact Current Rating (Max) 5 A Termination Features Rectangular Termination Post & Tail Thickness 2 mm[.008 in] Rectangular Termination Post & Tail Width 3 mm[.012 in] Termination Method to Printed Circuit Board Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length Mating Alignment With	PCB Contact Termination Area Plating Material Finish	Matte
PCB Contact Termination Area Plating Material Contact Base Material Contact Mating Area Plating Material Contact Mating Area Plating Material Contact Mating Area Plating Material Thickness .2 \(\mu\mathbb{m}[8 \muin] \) Contact Type Socket Contact Current Rating (Max) .5 A Termination Features Rectangular Termination Post & Tail Thickness .2 mm[.008 in] Rectangular Termination Post & Tail Width .3 mm[.012 in] Termination Method to Printed Circuit Board Surface Mount Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length Mating Alignment With	Contact Shape & Form	Square
Contact Base Material Copper Alloy Contact Mating Area Plating Material Gold Contact Mating Area Plating Material Thickness .2 µm[8 µin] Contact Type Socket Contact Current Rating (Max) .5 A Termination Features Rectangular Termination Post & Tail Thickness .2 mm[.008 in] Rectangular Termination Post & Tail Width .3 mm[.012 in] Termination Method to Printed Circuit Board Surface Mount Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length .5 mm[.02 in] Mating Alignment With	Contact Mating Area Plating Material Finish	Matte
Contact Mating Area Plating Material Contact Mating Area Plating Material Thickness .2 µm[8 µin] Contact Type Socket Contact Current Rating (Max) .5 A Termination Features Rectangular Termination Post & Tail Thickness Rectangular Termination Post & Tail Width .3 mm[.012 in] Termination Method to Printed Circuit Board Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length Mating Alignment With	PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness .2 µm[8 µin] Contact Type Socket Contact Current Rating (Max) .5 A Termination Features Rectangular Termination Post & Tail Thickness .2 mm[.008 in] Rectangular Termination Post & Tail Width .3 mm[.012 in] Termination Method to Printed Circuit Board Surface Mount Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length .5 mm[.02 in] Mating Alignment With	Contact Base Material	Copper Alloy
Contact Type Socket Contact Current Rating (Max) .5 A Termination Features Rectangular Termination Post & Tail Thickness .2 mm[.008 in] Rectangular Termination Post & Tail Width .3 mm[.012 in] Termination Method to Printed Circuit Board Surface Mount Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length .5 mm[.02 in] Mating Alignment With	Contact Mating Area Plating Material	Gold
Contact Current Rating (Max) Termination Features Rectangular Termination Post & Tail Thickness Rectangular Termination Post & Tail Width .3 mm[.012 in] Termination Method to Printed Circuit Board Surface Mount Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length Mating Alignment With	Contact Mating Area Plating Material Thickness	.2 μm[8 μin]
Termination Features Rectangular Termination Post & Tail Thickness .2 mm[.008 in] Rectangular Termination Post & Tail Width .3 mm[.012 in] Termination Method to Printed Circuit Board Surface Mount Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length .5 mm[.02 in] Mating Alignment With	Contact Type	Socket
Rectangular Termination Post & Tail Thickness .2 mm[.008 in] Rectangular Termination Post & Tail Width .3 mm[.012 in] Termination Method to Printed Circuit Board Surface Mount Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length .5 mm[.02 in] Mating Alignment With	Contact Current Rating (Max)	.5 A
Rectangular Termination Post & Tail Width .3 mm[.012 in] Termination Method to Printed Circuit Board Surface Mount Mechanical Attachment PCB Mount Alignment Type Positioning Bosses Locating Post Length .5 mm[.02 in] Mating Alignment With	Termination Features	
Termination Method to Printed Circuit Board Mechanical Attachment PCB Mount Alignment Type Locating Post Length Mating Alignment With	Rectangular Termination Post & Tail Thickness	.2 mm[.008 in]
Mechanical AttachmentPCB Mount Alignment TypePositioning BossesLocating Post Length.5 mm[.02 in]Mating AlignmentWith	Rectangular Termination Post & Tail Width	.3 mm[.012 in]
PCB Mount Alignment Type Locating Post Length .5 mm[.02 in] Mating Alignment With	Termination Method to Printed Circuit Board	Surface Mount
Locating Post Length .5 mm[.02 in] Mating Alignment With	Mechanical Attachment	
Mating Alignment With	PCB Mount Alignment Type	Positioning Bosses
	Locating Post Length	.5 mm[.02 in]
	Mating Alignment	With
Mating Alignment Type Polarization	Mating Alignment Type	Polarization
PCB Mount Retention Without	PCB Mount Retention	Without
PCB Mount Alignment With	PCB Mount Alignment	With
Connector Mounting Type Board Mount	Connector Mounting Type	Board Mount
Housing Features	Housing Features	
Mating Entry Location Top	Mating Entry Location	Тор



Centerline (Pitch)	.8 mm[.031 in]
Housing Material	Matte
Dimensions	
Connector Height	5 mm[.197 in]
Stack Height	5 mm, 6 mm, 7 mm, 8 mm[.197 in][.236 in][. 276 in][.315 in]
Usage Conditions	
Housing Temperature Rating	High
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Operation/Application	
Assembly Process Feature	Pick and Place Cover
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
	.5 in
Packaging Quantity	700
Packaging Type	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | Free Height



Customers Also Bought



















Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5177985-6_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5177985-6_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5177985-6_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Fine Pitch Stacking Connectors - 0.8mm Free Height (FH) Connectors

English

Product Specifications

Product Specification

English

Product Specification

English

Product Environmental Compliance

TE Material Declaration

English