
# 5084616-4 - ACTIVE

## Free Height

TE Internal #: 5084616-4 PCB Mount Receptacle, Vertical, Board-to-Board, 100 Position, .031 in [.8 mm] Centerline, Gold, Surface Mount, Signal, Natural, Free Height

#### View on TE.com >

Connectors > PCB Connectors > PCB Headers & Receptacles > Free Height Receptacle Conn: Board-Board, Vertical, 100, 0.8mm



PCB Connector Assembly Type: PCB Mount Receptacle

PCB Mount Orientation: Vertical

Connector System: Board-to-Board

Number of Positions: 100

Centerline (Pitch): .8 mm [ .031 in ]

All Free Height Receptacle Conn: Board-Board, Vertical, 100, 0.8mm (24)



## Features

## Product Type Features

PCB Connector Assembly Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Stackable	Yes
PCB Mount Orientation	Vertical
Number of Positions	100
Board-to-Board Configuration	Parallel
Electrical Characteristics	
Dielectric Withstanding Voltage (Max)	500 VAC
Insulation Resistance	2 ΜΩ

**C** For support call+1 800 522 6752

PCB Mount Receptacle, Vertical, Board-to-Board, 100 Position, .031 in [.8 mm] Centerline, Gold, Surface Mount, Signal, Natural, Free Height



Operating Voltage	100 VAC
Body Features	
Assembly Process Feature Material	Steel
Primary Product Color	Natural
Contact Features	
Contact Layout	Inline
PCB Contact Termination Area Plating Material Thickness	2 µm[78.74 µin]
Mating Tab Width	.4 mm[.016 in]
Mating Tab Thickness	.2 mm[.008 in]
PCB Contact Termination Area Plating Material Finish	Matte
Contact Shape & Form	Square
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	.2 µm[8 µin]
Contact Type	Socket
Contact Current Rating (Max)	.5 A

## **Termination Features**

Rectangular Termination Post & Tail Thickness	.2 mm[.008 in]
Rectangular Termination Post & Tail Width	.3 mm[.012 in]
Termination Method to Printed Circuit Board	Surface Mount
Mechanical Attachment	
PCB Mount Alignment Type	Positioning Bosses
Locating Post Length	.5 mm[.02 in]
Mating Alignment	With
Mating Alignment Type	Polarization
PCB Mount Retention	Without
PCB Mount Alignment	With
Connector Mounting Type	Board Mount
Housing Features	
Mating Entry Location	Тор
Centerline (Pitch)	.8 mm[.031 in]

**C** For support call+1 800 522 6752

07/29/2022 02:12AM | Page 2

PCB Mount Receptacle, Vertical, Board-to-Board, 100 Position, .031 in [.8 mm] Centerline, Gold, Surface Mount, Signal, Natural, Free Height



Housing Material	Matte
Dimensions	
Connector Height	13 mm[.512 in]
Stack Height	13 mm, 14 mm, 15 mm, 16 mm[.512 in][.551 in][.591 in][.63 in]
Usage Conditions	
Housing Temperature Rating	High
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Operation/Application	
Assembly Process Feature	Pick and Place Cover
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
	.5 in
Packaging Quantity	200
Packaging Type	Tape & Reel

## Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C
Product Compliance Disclaimer	

PCB Mount Receptacle, Vertical, Board-to-Board, 100 Position, .031 in [.8 mm] Centerline, Gold, Surface Mount, Signal, Natural, Free Height



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**





TE Part # 84615-4 0.8FH,P06H.5,100,30/SP,TU

Also in the Series | Free Height



# **Customers Also Bought**



PCB Mount Receptacle, Vertical, Board-to-Board, 100 Position, .031 in [.8 mm] Centerline, Gold, Surface Mount, Signal, Natural, Free Height





## Documents

## Product Drawings 0.8FH,R13H.5,100,08/Sn,TR,SC

English

## **CAD** Files

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_5084616-4\_R.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5084616-4\_R.3d\_igs.zip

English

Customer View Model

## ENG\_CVM\_CVM\_5084616-4\_R.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Fine Pitch Stacking Connectors - 0.8mm Free Height (FH) Connectors

English

**Product Specifications** 

Product Specification

English

**Product Specification** 

English

Product Environmental Compliance MD\_5084616-4\_053020182250\_dmtec

English

MD\_5084616-4\_053020182250\_dmtec

English