

53112-1 ✓ ACTIVE


TE Internal #: 53112-1

Splices, 20 – 16 AWG Wire Size, .5 – 1.25 mm² Wire Size, Serrated, 8 Serration, Length 1.63 in [41.1 mm], Bag, Open, Discrete Wire, Uninsulated

[View on TE.com >](#)



Terminals & Splices > Splices



Wire Size: .5 – 1.25 mm²

Sealable: No

Terminal Material Thickness: .51 mm [.021 in]

Serrated: Yes

Features

Product Type Features

Discrete Wire Type	Stranded
Sealable	No
Serrated	Yes
Wire Insulation Support Retention Type	Non-Insulation Support

Configuration Features

Number of Serrations	8
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Contact Plating Material	Silver
Barrel Type	Open

Termination Features

Termination Method	Crimp
--------------------	-------

Mechanical Attachment

Wire Insulation Support	Without
-------------------------	---------

Dimensions



Wire Size	.5 – 1.25 mm ²
Terminal Material Thickness	.51 mm[.021 in]
Overall Product Length	41.1 mm[1.63 in]

Usage Conditions

Insulation Option	Uninsulated
-------------------	-------------

Operation/Application

Heavy Duty	No
------------	----

Industry Standards

Government Qualified Splice	No
-----------------------------	----

Packaging Features

Packaging Quantity	100
Packaging Method	Bag

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on

requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Customers Also Bought



Documents

Product Drawings

FLAG RELAY, SPECIAL-RR 20-16

English

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_53112-1_Z.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_53112-1_Z.3d_igs.zip](#)

53112-1

Splices, 20 – 16 AWG Wire Size, .5 – 1.25 mm² Wire Size, Serrated, 8 Serration, Length 1.63 in [41.1 mm], Bag, Open, Discrete Wire, Uninsulated



English

Customer View Model

[ENG_CVM_CVM_53112-1_Z.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[RADIATION_RESISTANT_PRE-INSULATED_TERMINALS_SPLICES](#)

English