




Terminals &amp; Splices &gt; Quick Disconnects

Quick Disconnect Terminal Type: **Receptacle**Wire Size: **.82 – 2.08 mm<sup>2</sup>**Mating Tab Width: **6.35 mm [ .25 in ]**Terminal Orientation: **Straight**

## Features

### Product Type Features

Terminates To	Wire & Cable
Wire Stop	No
Wire/Cable Type	Regular Wire
Insertion Force	High
Sealable	No

### Configuration Features

Connection Capacity	Single
---------------------	--------

### Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm [.25 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open



### Mechanical Attachment

Mating Retention Type	Locking Lance
Wire Insulation Support	With

### Dimensions

Accepts Wire Insulation Diameter Range	3.9 mm[.154 in]
Overall Length	20.39 mm[.803 in]
Receptacle Terminal Stock Thickness	.46 mm[.018 in]
Wire Size	.82 – 2.08 mm <sup>2</sup>

### Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

### Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

### Packaging Features

Packaging Quantity	2400
Packaging Method	Strip/Reel

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as

EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

## Compatible Parts



TE Part # 640418-1  
BLADE REC 250 18-14AWG BR



TE Part # 2305570-1  
TERMINAL CUTTER, SIDE FEED



TE Part # 2-2266591-1  
OCEAN-2.0-APPLICATOR-S-110F220F



TE Part # 2-2266591-2  
OCEAN-2.0-APPLICATOR-S-110F220F



TE Part # 2266591-1  
OCEAN-2.0-APPLICATOR-S-110F220F



TE Part # 2266591-2  
OCEAN-2.0-APPLICATOR-S-110F220F



TE Part # 5-2266591-1  
OCEAN-2.0-APPLICATOR-S-110F220F



TE Part # 5-2266591-2  
OCEAN-2.0-APPLICATOR-S-110F220FA



TE Part # 7-2266591-1  
OCEAN-2.0-APPLICATOR-S-110F220F




TE Part # 7-2266591-2  
OCEAN-2.0-APPLICATOR-S-110F220F




TE Part # 7-2266591-7  
OCEAN\_2.0\_SPARE\_PART\_KIT-110F220F


## Also in the Series | FASTIN-FASTON 250




Crimp Terminal Housings(218)



Insertion & Extraction Tools(2)





PCB Terminals(2)



Quick Disconnects(255)

## Customers Also Bought



## Documents

### Product Drawings

[BLADE REC 250 18-14AWG BR](#)

English

### CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_640417-1\\_AG\\_c-640417-1-ag.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_640417-1\\_AG\\_c-640417-1-ag.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_640417-1\\_AG\\_c-640417-1-ag.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.



### Datasheets & Catalog Pages

[FASTIN\\_FASTON\\_Product\\_Line](#)

English

---

### Product Specifications

[Application Specification](#)

English

[Special 250 Blade Receptacle Terminal](#)

English

---

### Product Environmental Compliance

[MD\\_640417-1\\_02282018022\\_dmtec](#)

English

[MD\\_640417-1\\_02282018022\\_dmtec](#)

English