NOTES:

- I. MATERIAL : PHOSPHOR BRONZE.
- 2. UNDER PLATING : I.27um MIN NICKEL UNDERPLATE.
- 3. BOTH ENDS OF TIPS NOT PLATED UNLESS A SUFFIX 'P' IS ADDED AT THE END OF THE PART NUMBER.
- 4. A SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION.

spec ref				dr	Andrew Yong		2010/10/21		proje	ction	
	tolerance std	T 0 1 F 1			eng	Guo-Min Sun		2013/05/10			\square
ISO 406 ISO IIOI TOLERANCES U OTHERWISE SPE			chr	-		-					
			appr	Rick Bian		2013/05/13		product famil			
			0.X	± 0.35	E		●	5 ~ ~ ~	SQUAR		1
	surface/	linear	0.XX	±0.25			$^{-}_{+}$ U.	JIIII	JUUAR		N
	\checkmark		0.XXX	±0.10		Y	+ 0.5	mm S	QUARE P	I N	
	ISO I302	angular	0°	±°	www.	fci.com	cat.no).		-	
	2						3		PDS: Rev :	:CL	

Pro/E File - REV C - 2009-06-09

В

С

[]

Copyright FCI

D

А

n	N/	Μ	size	scale		Г
1	l Iv	V	А З	10:1		L
j	-		ecn no	ELX-N-147	719-1	
lу		MINITEK	rel level	Rele	ased	
		dwg no	86446	ò	r e v CL	
Pro	oduct –	Customer	Drw	sheet I of	2	

STATUS:Released

Printed: May 13, 2013

А

В

С


					2			3		
	PRODUCT NO	DIM X	PRODUCT NO	DIM X	PRODUCT NO	DIM X	PRODUCT NO	DIM X	PLATIN	G
	86446-X0I	8.45	86446-X34	5.80	86446-X67	13.20	63464-X0I	15.60	0	
	- X 0 2	9.55	- X 3 5	12.20	- X 6 8	4.00	- X 0 2	7. 0		
	- X 0 3	13.55	- X 3 6	7.80	- X 6 9	5.10	- X 0 3	21.10	2	
	- X 0 4	6.21	- X 3 7	.80	- X 7 0	24.10	- X 0 4	19.60	3	
А	- X O 5	7.31	- X 38	10.95	- X 7 I	9.27	- X 0 5	15.64	4	
	- X 0 6	.3	- X 3 9	19.05	- X 7 2	11.20	- X 0 6	13.65	5	
	- X 0 7	12.95	- X 4 0	2.45	- X 7 3	9.70	- X 0 7	15.05	6	
	- X 0 8	12.70	- X 4	15.24	- X 7 4	12.00	- X 0 8	19.05	7	
	- X 0 9	7.50	- X 4 2	17.85	- X 7 5	11.63	- X 0 9	25.32	8	
	- X I O	.90	- X 4 3	3.50	- X 7 6	7.10	- X I O	30.00		
	- X	5.60	- X 4 4	10.70	- X 7 7	15.00	- X	22.20		
	- X I 2	6.30	- X 4 5	4.70	- X 7 8	4.70	- X I 2	16.10		
	- X I 3	10.20	- X 4 6	16.55	- X 7 9	12.30	- X 3	25.00		
	- X 4	10.06	- X 4 7	20.50	- X 8 0	17.30				
	- X I 5	6.00	- X 4 8	15.90	- X 8	10.30				
	- X 6	8.55	- X 4 9	3.36	- X 8 2	11.50	_		PART NUM	
В	- X 7	12.55	- X 5 0	4.30	- X 8 3	21.70				
	- X 8	8.95	- X 5 I	22.00	- X 8 4	9.80				
	- X 9	9.05	- X 5 2	5.50	- X 8 5	18.30			<u>X</u> X	(X X X
	- X 2 0	13.05	- X 5 3	6.40	- X 8 6	16.30				
	- X 2 I	14.50	- X 5 4	4.00	- X 8 7	2. 0				
	- X 2 2	10.50	- X 5 5	4.40	- X 8 8	0.0			BASE P/N —	
	- X 2 3	8.00	- X 5 6	9.90	- X 8 9	4 . 40	_			
	- X 2 4	7.00	- X 5 7	8.10	- X 9 0	19.40	_			
	- X 2 5	6.50	- X 5 8		- X 9	24.40	_			
	- X 2 6	5.00	- X 5 9		- X 9 2	17.55	_			
	- X 2 7	4. 0	- X 6 0		- X 9 3	8.30	_			
С	- X 2 8	20.30	- X 6	6.12	- X 9 4	7.90	_			
	- X 2 9	13.85	- X 6 2	6.60	- X 9 5	15.50	_			
	- X 3 0	8.20	- X 6 3	6.70	- X 9 6	18.00	_			
	- X 3 I	17.00	- X 6 4		- X 9 7	.40	_			
J	- X 3 2	8.80	- X 6 5		- X 9 8	4.80				
	- X 3 3	10.80	- X 6 6	6.80	- X 9 9	18.90				

D

spec ref				dr	Andrew Yong		2010/10/21		proje	ection
tolerance std	T 0 1 5 1			eng	Guo-Min Sun	Guo-Min Sun				
ISO 406		RANCES L VISE SPE		chr	-		-		\square	
ISO 1101		INCL OIL		appr	Rick Bian		2013/05/13		product	famil
		0.X	± 0.35	ſ		●	5000			d
surface -	linear	0.XX	± 0.25		Ċj	$ ^{-}_{+}$ U.	JUIU	SQUAR		N
		0.XXX	±0.10]	Y	+ 0.5	mm	SQUARE P	I N	
ISO I302	angular	0°	±°	www	.fci.com	cat.no).		-	
2						З		PDS: Rev :	·CI	
L						0		PDS. Rev	.02	

IG	DESCRIPTION
	8 u″Au
	30 u" Au
	UN ASSIGNED
	l5 u"Au
	UN ASSIGNED
	I5 u"GXT
	30 u" GXT
	80-240u" Sn
	6u"GXT

MBER DESCRIPTION





STATUS:Released

Printed: May 13, 2013

А

В

С