


AMP | AMP Type IV TE Internal #: 66580-1 Power Contacts, Contact, 250 VAC, 250 VDC, Tin, 18 – 16 AWG Wire Size, .8 – 1.4 mm<sup>2</sup> Wire Size, Wire-to-Wire, 1 Position, Wire & Cable, AMP Type IV

View on TE.com >

Connectors > Power Connectors > Power Contacts



Power Contact Type: Contact Operating Voltage: 250 VDC Contact Mating Area Plating Material: Tin Wire Size: 18–16 AWG

### Features

#### **Product Type Features**

Power Contact Type	Contact
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable



#### **Configuration Features**

Number of Positions	1
Electrical Characteristics	
Test Current	13 A
Operating Voltage	250 VDC
Contact Features	
Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	1.8 A
Contact Type	Socket
Contact Retention Within Housing	With
Mating Pin Diameter	1.57 mm[.062 in]
Contact Base Material	Brass
Contact Mating Area Plating Material Thickness	1.02 μm[40 μin]
Contact Mating Area Plating Material Finish	Semi-Bright
Wire Contact Termination Area Plating Thickness	1 – 3 μm[40 – 118 μin]

#### 66580-1

Power Contacts, Contact, 250 VAC, 250 VDC, Tin, 18 – 16 AWG Wire Size, .8 – 1.4 mm<sup>2</sup> Wire Size, Wire-to-Wire, 1 Position, Wire & Cable, AMP Type IV



Wire Contact Termination Area Plating Material	Tin
Wire Contact Termination Area Plating Material Finish	Bright
Contact Orientation	Straight
Contact Size	16
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Connector Mounting Type	Panel Mount
Wire Insulation Support	With
Dimensions	
Wire Size	.8 – 1.4 mm <sup>2</sup>
Accepts Wire Insulation Diameter Range	2.03 – 2.54 mm[.08 – .1 in]
Usage Conditions	
Operating Temperature Range	-55 – 90 °C[-67 – 194 °F]
Operation/Application	
Circuit Application	Signal

## Packaging Features

Packaging Method	Strip
Other	
Wire/Cable Type	Discrete Wire
For Use With	G Series Connectors
Comment	Wire strip length 3.96 [.156] for all wire sizes.

# Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold:

#### 66580-1

Power Contacts, Contact, 250 VAC, 250 VDC, Tin, 18 – 16 AWG Wire Size, .8 – 1.4 mm<sup>2</sup> Wire Size, Wire-to-Wire, 1 Position, Wire & Cable, AMP Type IV



#### Not Yet Reviewed

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Not applicable for solder process capability

Halogen Content

Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


# **Compatible Parts**



 TE Part # 58495-2
 TE Part # 91505-1
 TE Part # 58495-1

 PROCRIMPER DIE ASSY MULTIMATE
 CCII TYPE III+ 24-16 ASSY
 PRO CRIMPER ASSY MULTIMATE

# Also in the Series | AMP Type IV



**Customers Also Bought** 

#### 66580-1

Power Contacts, Contact, 250 VAC, 250 VDC, Tin, 18 – 16 AWG Wire Size, .8 – 1.4 mm<sup>2</sup> Wire Size, Wire-to-Wire, 1 Position, Wire & Cable, AMP Type IV





#### Documents

Product Drawings TYPE VI SKT CONT,M-MATE

English

CAD Files 3D PDF

3D

Customer View Model ENG\_CVM\_CVM\_66580-1\_AN\_c-66580-1-an.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_66580-1\_AN\_c-66580-1-an.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_66580-1\_AN\_c-66580-1-an.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Instruction Sheets Instruction Sheet (U.S.) Japanese Instruction Sheet (U.S.)

English