

63963-1 ✓ ACTIVE

FASTON | FASTON 250


TE Internal #: 63963-1

Quick Disconnects, Receptacle, 18 – 14 AWG Wire Size, .82 – 2.08 mm² Wire Size, Mating Tab Width .25 in [6.35 mm], Flag, Steel, FASTON 250

[View on TE.com >](#)



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: .82 – 2.08 mm²

Mating Tab Width: 6.35 mm [.25 in]

Mating Tab Thickness: .81 mm [.032 in]

Features

Product Type Features

Terminates To	Wire & Cable
Wire/Cable Type	Regular Wire
Wire Stop	No
Insertion Force	Low
Sealable	No

Configuration Features

Connection Capacity	Single
---------------------	--------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm [.25 in]
Mating Tab Thickness	.81 mm [.032 in]
Terminal Orientation	Flag
Contact Base Material	Steel
Terminal Plating Material	Nickel
Crimp Type	F-Crimp



Barrel Type	Open
-------------	------

Mechanical Attachment

Mating Retention Type	Dimple
Wire Insulation Support	With

Dimensions

Accepts Wire Insulation Diameter Range	2.79 – 5.08 mm [.11 – .2 in]
Receptacle Terminal Stock Thickness	.41 mm [.016 in]
Overall Length	13.72 mm [.54 in]
Wire Size	.82 – 2.08 mm ²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 250 °C [-40 – 482 °F]

Industry Standards

CSA Certified	Yes
UL Rating	Listed

Packaging Features

Packaging Quantity	11000
Packaging Method	Strip/Reel

Other

Line	Budget
Comment	Left handed flag.

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1-1969705-1
250 FASTON HSG.,FLAG,REC.,3 POS,
NATURAL



TE Part # 1-1969706-1
250 FASTON HSG.,FLAG,REC.,2 POS,
BLACK



TE Part # 2-2150129-2
OCEAN_2.0_Applicator-S-110F1800



TE Part # 2150129-2
OCEAN_2.0_Applicator-S-110F1800




TE Part # 7-2150129-2
OCEAN_2.0_Applicator-S-110F1800




KIT
REPRESENTATION ONLY

TE Part # 7-2150129-7
OCEAN_2.0_SPARE_PART_KIT-
110F1800


Also in the Series | FASTON 250



Compression Connectors(4)



Crimp Terminal Housings(143)



Insertion & Extraction Tools(6)



Magnet Wire Terminals(1)



PCB Terminals(144)




Quick Disconnects(456)



Splices(4)

Customers Also Bought

TE Part #1971782-2
PTL TAB CONTACT, 14 AWGTE Part #7-1971876-7
PTL 3X5 PLUG HSG HIGH TEMP KEY
C BLKTE Part #61944-1
250 FASTON REC 18-14 AWG BRTE Part #63604-1
250 FASTON FLAG REC 18-12 AWG
NPSTTE Part #1969657-1
250 FASTON HSG., FLAG, REC., 1 POS,
BLACKTE Part #1744188-1
HSG ASY, ULTRASON WELD, 15/30/45
WINGSTE Part #2-1803060-2
ANVIL, COMBINATION, END FEED
WINGSTE Part #3-456402-0
CRIMPER, WIRE .055" FTE Part #8-240693-1
ANVIL

TE Part #2-1546111-6

Documents

Product Drawings

250 FASTON FLAG REC 18-14 AWG NPST

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_63963-1_H.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_63963-1_H.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_63963-1_H.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[82004 FASTON Terminals \(Insulated and Uninsulated\) Catalog - FASTON Receptacles Section](#)

English

Product Specifications

[Application Specification](#)

English

Product Environmental Compliance

[MD_63963-1_062920151233_dmtec](#)

English

[MD_63963-1_062920151233_dmtec](#)

English