

### MTA 100

TE Internal #: 647000-2

Standard Rectangular Connectors, Connector Assembly, Plug, Mating Alignment, Polarization Mating Alignment Type, Mating


Retention, MTA 100

View on TE.com >



Connectors > Rectangular Connectors > Standard Rectangular Connectors > Nylon Tin Plated Plug: 2.54mm, With Mating Alignment, MTA 100











Connector Product Type: Connector Assembly

Connector & Housing Type: Plug

Mating Alignment: With

Mating Alignment Type: Polarization

Mating Retention: With

All Nylon Tin Plated Plug: 2.54mm, With Mating Alignment, MTA 100 (81)

## **Features**

### **Product Type Features**

| Product Type Features             |                    |
|-----------------------------------|--------------------|
| Product Style                     | Assembly           |
| Shape                             | Rectangular        |
| Wire/Cable Type                   | Stranded           |
| Connector Type                    | Connector Assembly |
| Connector Product Type            | Connector Assembly |
| Connector & Housing Type          | Plug               |
| Connector System                  | Wire-to-Wire       |
| Insertion Force Type              | Normal             |
| Sealable                          | No                 |
| Connector & Contact Terminates To | Wire & Cable       |
| Configuration Features            |                    |
| Number of Cavities                | 2                  |

2

Number of Positions



| Number of Rows                                 | 1                             |
|--|-------------------------------|
| Panel Gasket                                   | Without                       |
| Electrical Characteristics                     |                               |
| Operating Voltage                              | 250 VAC                       |
| Contact Features                               |                               |
| Contact Layout                                 | In-line                       |
| Contact Type                                   | Tab                           |
| Wire Contact Termination Area Plating Material | Tin                           |
| Contact Underplating Material                  | Nickel                        |
| Contact Mating Area Plating Material           | Tin                           |
| Contact Retention Within Housing               | With                          |
| Contact Current Rating (Max)                   | 5 A                           |
| Termination Features                           |                               |
| Termination Method to Wire & Cable             | Insulation Displacement (IDC) |
| Mechanical Attachment                          |                               |
| Panel Mount                                    | No                            |
| Contact Retention Type Within Housing          | Locking Lance                 |
| Panel Mount Feature                            | Without                       |
| Mating Alignment                               | With                          |
| Mating Alignment Type                          | Polarization                  |
| Mating Retention                               | With                          |
| Mating Retention Type                          | Latch                         |
| Connector Mounting Type                        | Cable Mount (Free-Hanging)    |
| Housing Features                               |                               |
| Housing Color                                  | Red                           |
| Housing Material                               | Nylon 6/6                     |
| Centerline (Pitch)                             | 2.54 mm[.1 in]                |
| Dimensions                                     |                               |
| Width  | 21.4 mm[.843 in]              |
| Height   | 12.54 mm[.494 in]             |
| Length   | 7.62 mm[.3 in]                |
| Wire Size                                      | .3 – .4 mm²                   |



## **Usage Conditions**

| Operating Temperature Range | -55 – 105 °C[-67 – 221 °F] |
|-----------------------------|----------------------------|
| Operation/Application       |                            |
| Shielded                    | No                         |
| Circuit Application         | Signal                     |
| Industry Standards          |                            |
| CSA Rating                  | Certified                  |
| Agency/Standard             | CSA, UL                    |
| UL Rating                   | Recognized                 |
| CSA File Number             | LR 7189                    |
| UL File Number              | E28476                     |
| UL Flammability Rating      | UL 94V-2                   |
| Packaging Features          |                            |
| Packaging Quantity          | 300                        |

Bag/Box

## **Product Compliance**

Packaging Method

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per<br>homogenous material. Also BFR/CFR/PVC<br>Free                                       |
| Solder Process Capability                     | Not applicable for solder process capability  |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts



TE Part # CAT-104MTA-NTPNR

Nylon Tin Plated Receptacle: 2.54mm,

No Mating Alignment, MTA 100



TE Part # 640550-2 02P MTA100 COVER



TE Part # CAT-104MTA-NYLCC Nylon PCB Connector Covers: 2.54 mm, MTA 100



TE Part # 58074-1 MTA 50/100/156 MANUAL TOOL FRAME



TE Part # 3-644574-2 02P MTA100 CONN ASSY BLK LF



TE Part # 58638-1 MTA 100 CRIMP HEAD PRODUCTION POSTED



TE Part # 58639-1 MTA 100 POSTED MANUAL TOOL ASSEMBLY

# Also in the Series | MTA 100



Insertion & Extraction Tools(2)



PCB Connector Covers(107)



PCB Connector Keying(1)



PCB Headers & Receptacles(1182)



Standard Rectangular Connectors (1718)



Wire-to-Board Connector Assemblies & Housings(1)



Wire-to-Board Connector Contacts(18)

# Customers Also Bought






TE Part #1-640455-2 12P MTA100 HDR ASSY SQ R/A POL



TE Part #3-641435-4 04P MTA156 CONN ASSY ORNG








TE Part #3-641435-6 06P MTA156 CONN ASSY ORNG









### **Documents**

## **Product Drawings**

02P MTA100 PSTD CONN ASSY SN

English

### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_647000-2\_F.2d\_dxf.zip

English

## 3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_647000-2\_F.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_647000-2\_F.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages



## MTA, CST-100 II, SL-156 and AMP Economy Power (EP) Connectors

English

Agency Approvals

Agency Approval Document

English