#### **AMP**

TE Internal #: 66741-5

Power Contacts, Contact, Gold, 10 AWG Wire Size,  $5-6~\text{mm}^2$  Wire Size, Wire-to-Wire, Wire & Cable, Crimp, Power, Socket, -55 – 125  $^\circ$ 

C [-67 – 257 °F]

View on TE.com >



Connectors > Power Connectors > Power Contacts



Power Contact Type: Contact

Contact Mating Area Plating Material: Gold

Wire Size: 5 – 6 mm<sup>2</sup>

Connector System: Wire-to-Wire

### **Features**

### **Product Type Features**

| Power Contact Type                                    | Contact          |
|---|------------------|
| Connector System                                      | Wire-to-Wire     |
| Connector & Contact Terminates To                     | Wire & Cable     |
| Electrical Characteristics                            |                  |
| Test Current  | 35 A             |
| Contact Features                                      |                  |
| Contact Mating Area Plating Material                  | Gold             |
| Contact Current Rating (Max)                          | 35 A             |
| Contact Type  | Socket           |
| Mating Tab Width                                      | 5.84 mm[.23 in]  |
| Mating Tab Thickness                                  | 2.67 mm[.105 in] |
| Contact Base Material                                 | Copper           |
| Contact Mating Area Plating Material Thickness        | .76 μm[30 μin]   |
| Wire Contact Termination Area Plating Thickness       | .25 μm[10 μin]   |
| Wire Contact Termination Area Plating Material        | Gold             |
| Wire Contact Termination Area Plating Material Finish | Bright           |
| Contact Orientation                                   | Right Angle      |
| Contact Underplating Material                         | Copper           |



| Termination Method to Wire & Cable     | Crimp   |
|--|---|
| Mechanical Attachment                  |   |
| Wire Insulation Support                | With  |
| Dimensions                             |   |
| Wire Size                              | 5 – 6 mm <sup>2</sup>                                       |
| Accepts Wire Insulation Diameter Range | 4.83 – 5.59 mm[.19 – .22 in]                                |
| Usage Conditions                       |   |
| Operating Temperature Range            | -55 – 125 °C[-67 – 257 °F]                                  |
| Operation/Application                  |   |
| Circuit Application                    | Power   |
| Packaging Features                     |   |
| Packaging Method                       | Reel  |
| Packaging Quantity                     | 1500  |
| Other                                  |   |
| Wire/Cable Type                        | Discrete Wire   |
| For Use With                           | CPC Connectors, G Series Connectors, M<br>Series Connectors |

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant with Exemptions   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold  |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Pb (1.4% in BODY & NUT) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per<br>homogenous material. Also BFR/CFR/PVC<br>Free   |
| Solder Process Capability                     | Not applicable for solder process capability  |



#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



TE Part # 206037-2 CPC PLUG ASSEMBLY SIZE 17-3



TE Part # 90384-1 HHHT TYPE XII MALE FEMALE 10 ASSY



TE Part # 7-1579008-6 UNLOCKING TOOL



TE Part # 66253-2 MALE CONTACT ASSY. (STRIP)



# **Customers Also Bought**



TE Part #DT04-12PD-B016
DEUTSCH DT Series Housings &
Connectors

















#### **Documents**

#### **Product Drawings**

TYPE XII FEMALE CONT (STRIP)

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_66741-5\_W.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_66741-5\_W.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_66741-5\_W.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

AMP Circular Connectors for Commercial Signal & Power Applications

English

**Power Contacts** 

English

M\_SERIES\_PIN\_AND\_SOCKET\_CONNECTORS

English

Products for Aerospace and Defense

English

## **Product Specifications**

**Application Specification** 

English

#### **Product Environmental Compliance**

**Product Compliance** 

English

**Product Compliance** 

Power Contacts, Contact, Gold, 10 AWG Wire Size,  $5-6~\text{mm}^2$  Wire Size, Wire-to-Wire, Wire & Cable, Crimp, Power, Socket, -55-125~°C [-67 -257~°F]



English