



QUICK DISCONNECTS



✓ Active

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**

TE CONNECTIVITY (TE)

312 FAST REC 12-16 016 BR

FASTON | FASTON Terminals and Housings

63677-2

TE Internal Number: 63677-2

Always EU RoHS/ELV Compliant

Mating Tab Width **7.92 mm [.312 in]**

Mating Tab Thickness **.81 mm [.032 in]**

Wire Insulation Diameter (Max) **4.06 mm [.16 in]**

Wire Size (AWG) **16 – 12**

Wire Size (mm²) **1.25 – 3**

Product Drawings

[RECEPTACLE, FASTON, 7.92 \[.312\] SERIES](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[82004 FASTON Terminals \(Insulated And Uninsulated\) Catalog - FASTON Receptacles Section](#)

PDF
English

Product Specifications

Application Specification

[FASTON Straight Receptacles With "F-" Crimp Feature](#)

PDF
English

[Wire Preparation And Crimp Inspection Guide](#)

PDF
English

[Wire Preparation And Crimp Inspection Guide](#)

TIF
English

Product Type Features	Wire Stop	No
	Disconnect Type	Quick Disconnect
	Insertion Force	Low
	FASTON	Yes
	Wire/Cable Composition	Stranded
	Wire/Cable Type	Discrete Wire
	Insulated	No
	Insulated Wire Support	Yes
	Support Style	Insulation Support
Applies To	Wire/Cable	

Configuration Features	Terminal Angle	Straight
	Connection Capacity	Single
	2-Wire Insulation Diameter (Max per Wire)	2.79 mm [.11 in]

Body Features	Plating Material	Brass, Unplated
	Fully Insulated	Yes

Contact Features	Terminal Orientation	Straight
------------------	----------------------	-----------------

Termination Features	Crimp Type	F-Crimp
----------------------	------------	----------------

Dimensions	Mating Tab Width	7.92 mm [.312 in]
	Mating Tab Thickness	.81 mm [.032 in]
	Wire Insulation Diameter (Max)	4.06 mm [.16 in]
	Wire Size (AWG)	16 – 12
	Wire Size (mm ²)	1.25 – 3
	Material Thickness	.41 mm [.016 in]
	Overall Length	22.86 mm [.9 in]

Industry Standards	UL Rating	Recognized
	CSA Certified	Yes

Packaging Features	Packaging Method	Reel
	Packaging Quantity	6000

Other

Line

Premier

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)