06P MTA100 HDR ASSY,SM,FL,SN 🗸 ACTIVE


MTA | MTA 100

TE Part # 647166-6 TE Internal #: 647166-6

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Headers & Receptacles



PCB Connector Assembly Type: PCB Mount Header

PCB Mount Orientation: Vertical
Connector System: Wire-to-Board

Number of Positions: 6

Centerline (Pitch): 2.54 mm [.1 in]

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Unshrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

PCB Mount Orientation	Vertical
Number of Positions	6
Number of Rows	1

Electrical Characteristics

Contact Features

Contact Layout	Inline
Contact Underplating Material Thickness	1.27 μm[50 μin]
PCB Contact Termination Area Plating Material Thickness	3.81 – 6.3 μm[150 – 250 μin]
Mating Post Length	7.37 mm[.29 in]
PCB Contact Termination Area Plating Material Finish	Bright
Contact Shape	Square
Contact Underplating Material	Nickel



PCP Contact Tormination Area Plating Material	Tin-Lead
PCB Contact Termination Area Plating Material	
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Tin-Lead
Contact Mating Area Plating Material Thickness	3.81 – 6.3 μm[150 – 250 μin]
Contact Type	Pin
Contact Current Rating (Max)	5 A
Contact Transmits (Typical)	Power
Termination Features	
Termination Method to Wire & Cable	Solder
Termination Method to Printed Circuit Board	Surface Mount
Mechanical Attachment	
Strain Relief	Without
Mating Retention Type	Friction Lock
Mating Alignment	Without
Panel Mount Feature	Without
PCB Mount Alignment	Without
Mating Retention	With
PCB Mount Retention	Without
Connector Mounting Type	Board Mount
Contact Retention	Without
Housing Features	
Centerline (Pitch)	2.54 mm[.1 in]
Housing Color	Black
Housing Material	Nylon 4/6
Dimensions	
Connector Height	8.81 mm[.34 in]
PCB Thickness (Recommended)	.25 mm[.01 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Signal

Industry Standards



CSA Rating	Certified
UL Flammability Rating	UL 94V-0
Agency/Standard	CSA, UL
CSA File Number	LR7189
UL Rating	Recognized
UL File Number	E28476
Packaging Features	
Packaging Quantity	500
Packaging Method	Bag/Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2019 (197) Candidate List Declared Against: JAN 2019 (197)
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts





Standard Rectangular Connectors(36)



Wire-to-Board Connector Housings(1)

Also in the Series MTA 100



PCB Connector Covers (107)



PCB Connector Keying(1)



Standard Rectangular Connectors(1730)



Wire-to-Board Connector Contacts(18)



Wire-to-Board Headers & Receptacles(1216)

Customers Also Bought




TE Part #1-1571990-7 TSPD11FGRA004




TE Part #1-647166-0 AMPMODU 2.0mm PITCH, 10P MTA100 HDR ASSY, SM,FL,SN



TE Part #102156-5 024 UNIV HDR SP 4S 30DP STD




TE Part #2041051-1 AMPMODU 2.0mm PITCH, POST HDR




TE Part #1-2041051-4

POST HDR

TE Part #2041051-3 AMPMODU 2.0mm PITCH, POST HDR



TE Part #2170166-1 SFP 1X4 ANGLED CAGE & LIGHT PI



TE Part #3-641211-7 07P MTA100 HDR ASY PL STR LF





TE Part #6-146128-2 14 MODII HDR SR SFMNT B/A .100



Documents

Product Drawings

06P MTA100 HDR ASSY,SM,FL,SN

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_647166-6_M.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_647166-6_M.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_647166-6_M.3d_stp.zip

English

Datasheets & Catalog Pages

MTA, CST-100 II, SL-156 and AMP Economy Power (EP) Connectors

English

Product Environmental Compliance

TE Material Declaration

English

Agency Approvals

Agency Approval Document

English