





DO NOT SCALE DRAWING	 www.fciconnect.com	 ISO PROJECTION 5:1	SCALE
TITLE		 DIMENSION IN MILLIMETERS A3	DWG SIZE
Terminal 1.5 DCS2 Female	CATALOG NUMBER	 SHEET 1 of 1	
<small>THIS DRAWING AND ALL OTHER INFORMATION CONTAINED THEREIN IS PROPRIETARY AND THE PROPERTY OF FCI. This drawing may not be copied, reproduced or disclosed to any third party without the expressed written permission of FCI. © FCI April 1999</small>			

- Direct Links**
 - Cross Reference
 - RoHS/LF P/N search
 - Document & Drawing search
 - Application tooling
- Services**
 - Contact us
 - Distributor list
 - Pricing request
 - Order samples
- Literature**
 - Brochures & catalogs
 - Product documentation
 - Technical library

Start > Search=60000514* > **60000514**

60000514



60000514

DCS-2 female 1.5 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Assistant](#) [Add to Favorites](#)

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- [Price request](#)

Mating Half

[60100614](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
	Long Auxiliary Steel Spring in CrNi

Features	Suitable for Secondary Lock Low Contact Mating Force
Dimensional	
Contact Pitch	4 mm
Electrical	
Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	13
Resistance (Contact)	< 2
Mechanical	
Range of Wire Gauge Min - Max	0.2 - 0.35 mm ²
Contact mating force	< 7N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
Physical	
Plating	Au
Material	CuSn/CrNi
Environmental	
IMDS	No
Other Features	
Type	Female
Crimping Tool	65200411
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

Direct Links ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

Services ...

- Contact us
- Distributor list
- Pricing request
- Order samples

Literature ...

- Brochures & catalogs
- Product documentation
- Technical library

Start > Search=60000531* > **60000531**

60000531



60000531

DCS-2 female 1.5 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Assistant](#) [Add to Favorites](#)

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- [Price request](#)

Mating Half

[60100631](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
	Long Auxiliary Steel Spring in CrNi

Features	Suitable for Secondary Lock Low Contact Mating Force
Dimensional	
Contact Pitch	4 mm
Electrical	
Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	21
Resistance (Contact)	< 2
Mechanical	
Range of Wire Gauge Min - Max	0.5 - 1 mm ²
Contact mating force	< 7N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
Physical	
Plating	Sn
Material	CuFe/CrNi
Environmental	
IMDS	No
Other Features	
Type	Female
Crimping Tool	65200412
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

Direct Links ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

Services ...

- Contact us
- Distributor list
- Pricing request
- Order samples

Literature ...

- Brochures & catalogs
- Product documentation
- Technical library

Start > Search=60000534* > **60000534**

60000534



60000534

DCS-2 female 1.5 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Assistant](#) [Add to Favorites](#)

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- [Price request](#)

Mating Half

[60100634](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
	Long Auxiliary Steel Spring in CrNi

Features	Suitable for Secondary Lock Low Contact Mating Force
Dimensional	
Contact Pitch	4 mm
Electrical	
Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	21
Resistance (Contact)	< 2
Mechanical	
Range of Wire Gauge Min - Max	0.5 - 1 mm ²
Contact mating force	< 7N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
Physical	
Plating	Au
Material	CuSn/CrNi
Environmental	
IMDS	No
Other Features	
Type	Female
Crimping Tool	65200413
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

- Direct Links**
 - Cross Reference
 - RoHS/LF P/N search
 - Document & Drawing search
 - Application tooling
- Services**
 - Contact us
 - Distributor list
 - Pricing request
 - Order samples
- Literature**
 - Brochures & catalogs
 - Product documentation
 - Technical library

Start > Search=60000541* > **60000541**

60000541



60000541

DCS-2 female 1.5 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Assistant](#) [Add to Favorites](#)

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- [Price request](#)

Mating Half

[60100641](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
	Long Auxiliary Steel Spring in CrNi

Features	Suitable for Secondary Lock Low Contact Mating Force
Dimensional	
Contact Pitch	4 mm
Electrical	
Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	24
Resistance (Contact)	< 2
Mechanical	
Range of Wire Gauge Min - Max	> 1 - 1.5 mm ²
Contact mating force	< 7N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
Physical	
Plating	Sn
Material	CuFe/CrNi
Environmental	
IMDS	No
Other Features	
Type	Female
Crimping Tool	65200413
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

Direct Links ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

Services ...

- Contact us
- Distributor list
- Pricing request
- Order samples

Literature ...

- Brochures & catalogs
- Product documentation
- Technical library

Start > Search=60000611* > **60000611**

60000611



60000611

DCS-2 female 1.5 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Assistant](#) [Add to Favorites](#)

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- [Price request](#)

Mating Half

[60100711](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
	Long Auxiliary Steel Spring in CrNi

Features	Suitable for Secondary Lock Low Contact Mating Force
Dimensional	
Contact Pitch	4 mm
Electrical	
Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	16
Resistance (Contact)	< 2
Mechanical	
Range of Wire Gauge Min - Max	0.2 - 0.35 mm ²
Contact mating force	< 7N
Single Wire Seal Compatible	Yes
Contact unmating force	< 4N
Physical	
Plating	Sn
Material	CuFe/CrNi
Environmental	
IMDS	No
Other Features	
Type	Female
Crimping Tool	65200413
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

Direct Links ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

Services ...

- Contact us
- Distributor list
- Pricing request
- Order samples

Literature ...

- Brochures & catalogs
- Product documentation
- Technical library

Start > Search=60000614* > **60000614**

60000614



60000614

DCS-2 female 1.5 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Assistant](#) [Add to Favorites](#)

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- [Price request](#)

Mating Half

[60100714](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
	Long Auxiliary Steel Spring in CrNi

Features	Suitable for Secondary Lock Low Contact Mating Force
Dimensional	
Contact Pitch	4 mm
Electrical	
Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	16
Resistance (Contact)	< 2
Mechanical	
Range of Wire Gauge Min - Max	0.2 - 0.35 mm ²
Contact mating force	< 7N
Single Wire Seal Compatible	Yes
Contact unmating force	< 4N
Physical	
Plating	Au
Material	CuSn/CrNi
Environmental	
IMDS	No
Other Features	
Type	Female
Crimping Tool	65200413
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

Direct Links ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

Services ...

- Contact us
- Distributor list
- Pricing request
- Order samples

Literature ...

- Brochures & catalogs
- Product documentation
- Technical library

Start > Search=60000631* > **60000631**

60000631



60000631

DCS-2 female 1.5 mm terminal

ACTIVE

Customer Drawing

Automotive division

[Assistant](#) [Add to Favorites](#)

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- [Price request](#)

Mating Half

[60100731](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
	Long Auxiliary Steel Spring in CrNi

Features	Suitable for Secondary Lock Low Contact Mating Force
Dimensional	
Contact Pitch	4 mm
Electrical	
Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	2
Resistance (Contact)	< 2
Mechanical	
Range of Wire Gauge Min - Max	0.5 - 1 mm ²
Contact mating force	< 7N
Single Wire Seal Compatible	Yes
Contact unmating force	< 4N
Physical	
Plating	Sn
Material	CuFe/CrNi
Environmental	
IMDS	No
Other Features	
Type	Female
Crimping Tool	65200414
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

Direct Links ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

Services ...

- Contact us
- Distributor list
- Pricing request
- Order samples

Literature ...

- Brochures & catalogs
- Product documentation
- Technical library

Start > Search=60000634* > **60000634**

60000634



60000634

DCS-2 female 1.5 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Assistant](#) [Add to Favorites](#)

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- [Price request](#)

Mating Half

[60100734](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
	Long Auxiliary Steel Spring in CrNi

Features	Suitable for Secondary Lock Low Contact Mating Force
Dimensional	
Contact Pitch	4 mm
Electrical	
Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	2
Resistance (Contact)	< 2
Mechanical	
Range of Wire Gauge Min - Max	0.5 - 1 mm ²
Contact mating force	< 7N
Single Wire Seal Compatible	Yes
Contact unmating force	< 4N
Physical	
Plating	Au
Material	CuSn/CrNi
Environmental	
IMDS	No
Other Features	
Type	Female
Crimping Tool	65200410
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

Direct Links ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

Services ...

- Contact us
- Distributor list
- Pricing request
- Order samples

Literature ...

- Brochures & catalogs
- Product documentation
- Technical library

Start > Search=60000641* > **60000641**

60000641



60000641

DCS-2 female 1.5 mm terminal

ACTIVE

Customer Drawing

Automotive division

[Assistant](#) [Add to Favorites](#)

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- [Price request](#)

Mating Half

[60100741](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
	Long Auxiliary Steel Spring in CrNi

Features	Suitable for Secondary Lock Low Contact Mating Force
Dimensional	
Contact Pitch	4 mm
Electrical	
Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	24
Resistance (Contact)	< 2
Mechanical	
Range of Wire Gauge Min - Max	> 1 - 1.5 mm ²
Contact mating force	< 7N
Single Wire Seal Compatible	Yes
Contact unmating force	< 4N
Physical	
Plating	Sn
Material	CuFe/CrNi
Environmental	
IMDS	No
Other Features	
Type	Female
Crimping Tool	65200410
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.