

62253-2 ✓ ACTIVE

FASTON | FASTON 250


TE Internal #: 62253-2

Quick Disconnects, Receptacle, 14 – 10 AWG Wire Size, 2.08 – 5.26 mm² Wire Size, Mating Tab Width .25 in [6.35 mm], Piggyback, Brass, FASTON 250

[View on TE.com >](#)



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **2.08 – 5.26 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Terminates To	Wire & Cable
Wire/Cable Type	Regular Wire
Wire Stop	No
Insertion Force	Normal
Sealable	No

Configuration Features

Connection Capacity	Single
---------------------	--------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm [.25 in]
Mating Tab Thickness	.81 mm [.032 in]
Terminal Orientation	Piggyback
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp



Barrel Type	Open
-------------	------

Mechanical Attachment

Mating Retention Type	Dimple
Wire Insulation Support	With

Dimensions

Accepts Wire Insulation Diameter Range	3.81 – 5.08 mm [.15 – .2 in]
Receptacle Terminal Stock Thickness	.4 mm [.015 in]
Overall Length	19.56 mm [.77 in]
Wire Size	2.08 – 5.26 mm ²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C [-40 – 230 °F]

Industry Standards

CSA Certified	Yes
UL Rating	Listed

Packaging Features

Packaging Quantity	2000
Packaging Method	Strip/Reel

Other

Comment	Tab Thickness: 0.81 [.032]
---------	----------------------------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

Free












Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 <p>TE Part # 2305570-1 TERMINAL CUTTER, SIDE FEED</p>	 <p>KIT REPRESENTATION ONLY</p> <p>TE Part # 7-2266491-7 OCEAN_2.0_SPARE_PART_KIT-130F2200</p>	 <p>TE Part # 1-280079-2 250 FASTON,REC.,14-17AWG,TPBR</p>	 <p>TE Part # 735211-2 250 FASTON REC 14-10 AWG TPBR</p>
 <p>TE Part # 2-2266491-1 OCEAN-2.0-APPLICATOR-S-130F2200</p>	 <p>TE Part # 2-2266491-2 OCEAN-2.0-APPLICATOR-S-130F2200A</p>	 <p>TE Part # 2266491-1 OCEAN-2.0-APPLICATOR-S-130F2200</p>	 <p>TE Part # 2266491-2 OCEAN-2.0-APPLICATOR-S-130F2200A</p>
 <p>TE Part # 7-2266491-1 OCEAN-2.0-APPLICATOR-S-130F2200</p>	 <p>TE Part # 7-2266491-2 OCEAN-2.0-APPLICATOR-S-130F2200A</p>	 <p>REPRESENTATION ONLY</p> <p>TE Part # 90120 DAHT 250 FASTON REC 14-10 ASSY</p>	

Also in the Series | **FASTON 250**



Compression Connectors(4)



Crimp Terminal Housings(143)



Insertion & Extraction Tools(6)



Magnet Wire Terminals(1)



PCB Terminals(144)



Quick Disconnects(456)



Splices(4)

Customers Also Bought



TE Part #770003-3
UMNL II PIN PTPPHBZ




TE Part #41531
250 FASTON FLAG REC 18-12 AWG BR



TE Part #60851-1
250 FASTON REC 12-10 AWG TPBR




TE Part #40524
RING TERMINAL 12-10 AWG TPBR



TE Part #41473
SPADE TERMINAL 18-14 AWG TPBR



TE Part #41450
250 FASTON REC 14-10 AWG TPBR



TE Part #63306-2
250 FASTON REC 18-14 AWG TPBR



TE Part #1-1393212-6
T92S7D22-22



TE Part #1742550-1
250 FASTON,TAB,20-15 AWG,NPST



TE Part #1742556-1
RING RONGUE 15-22AWG NPST

Documents



Product Drawings

250 FASTON REC 14-10 TPBR

English

CAD Files

Customer View Model

[ENG_CVM_CVM_62253-2_AE.2d_dxf.zip](#)

English

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_62253-2_AE.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_62253-2_AE.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

82004 FASTON Terminals (Insulated and Uninsulated) Catalog - FASTON Receptacles Section

English

Product Specifications

Application Specification

English

Product Environmental Compliance

[MD_62253-2_05312018954_dmtec](#)

English

[MD_62253-2_05312018954_dmtec](#)

English

Agency Approvals

CSA Certificate

English

CSA Certificate

English