



DO NOT SCALE DRAWING	 <a href="http://www.fciconnect.com">www.fciconnect.com</a>	 ISO PROJECTION <b>5:1</b>	SCALE
TITLE		DIMENSION IN MILLIMETERS	DWG SIZE
<b>Terminal 1.5 DCS2 Male</b>		CATALOG NUMBER	SHEET
		--	<b>1</b> of <b>1</b>
<small>THIS DRAWING AND ALL OTHER INFORMATION CONTAINED THEREIN IS PROPRIETARY AND THE PROPERTY OF FCI. This drawing may not be copied, reproduced or disclosed to any third party without the expressed written permission of FCI. © FCI April 1999</small>			

- Direct Links**
  - Cross Reference
  - RoHS/LF P/N search
  - Document & Drawing search
  - Application tooling
- Services**
  - Contact us
  - Distributor list
  - Pricing request
  - Order samples
- Literature**
  - Brochures & catalogs
  - Product documentation
  - Technical library

[Back > 60100211](#)

[Assistant](#)



**60100211**

**DCS-2 male 1.5 mm terminal**

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#)  [Print Datasheet](#)

**FCI Brings You More**

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

**Specifications**

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

**General**

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

**Dimensional**

Contact Pitch	4 mm
---------------	------

**Electrical**

Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	13
Resistance (Contact)	< 2
<b>Mechanical</b>	
Range of Wire Gauge Min - Max	0.2 - 0.35 mm <sup>2</sup>
Contact mating force	< 7N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
<b>Physical</b>	
Plating	Sn
Material	CuFe/CrNi
<b>Environmental</b>	
IMDS	No
<b>Other Features</b>	
Type	Male
Crimping Tool	65200413
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

- Direct Links**
  - Cross Reference
  - RoHS/LF P/N search
  - Document & Drawing search
  - Application tooling
- Services**
  - Contact us
  - Distributor list
  - Pricing request
  - Order samples
- Literature**
  - Brochures & catalogs
  - Product documentation
  - Technical library

[Back > 60100231](#)

[Assistant](#)



**60100231**

**DCS-2 male 1.5 mm terminal**

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#)  [Print Datasheet](#)

**FCI Brings You More**

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

**Specifications**

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

**General**

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

**Dimensional**

Contact Pitch	4 mm
---------------	------

**Electrical**

Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	21
Resistance (Contact)	< 2
<b>Mechanical</b>	
Range of Wire Gauge Min - Max	0.5 - 1 mm <sup>2</sup>
Contact mating force	< 7N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
<b>Physical</b>	
Plating	Sn
Material	CuFe/CrNi
<b>Environmental</b>	
IMDS	No
<b>Other Features</b>	
Type	Male
Crimping Tool	65200413
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

**Direct Links** ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

**Services** ...

- Contact us
- Distributor list
- Pricing request
- Order samples

**Literature** ...

- Brochures & catalogs
- Product documentation
- Technical library

[Back > 60100611](#)

[Assistant](#)



**60100611**

**DCS-2 male 1.5 mm terminal**

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#)  [Print Datasheet](#)

**FCI Brings You More**

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

**Specifications**

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

**General**

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

**Dimensional**

Contact Pitch	4 mm
---------------	------

**Electrical**

Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	13
Resistance (Contact)	< 2
<b>Mechanical</b>	
Range of Wire Gauge Min - Max	0.2 - 0.35 mm <sup>2</sup>
Contact mating force	< 7N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
<b>Physical</b>	
Plating	Sn
Material	CuFe/CrNi
<b>Environmental</b>	
IMDS	No
<b>Other Features</b>	
Type	Male
Crimping Tool	65200411
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

- Direct Links**
  - Cross Reference
  - RoHS/LF P/N search
  - Document & Drawing search
  - Application tooling
- Services**
  - Contact us
  - Distributor list
  - Pricing request
  - Order samples
- Literature**
  - Brochures & catalogs
  - Product documentation
  - Technical library

[Back > 60100614](#)

[Assistant](#)



**60100614**

**DCS-2 male 1.5 mm terminal**

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#)  [Print Datasheet](#)

**FCI Brings You More**

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

**Specifications**

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

**General**

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

**Dimensional**

Contact Pitch	4 mm
---------------	------

**Electrical**



Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	13
Resistance (Contact)	< 2
<b>Mechanical</b>	
Range of Wire Gauge Min - Max	0.2 - 0.35 mm <sup>2</sup>
Contact mating force	< 7N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
<b>Physical</b>	
Plating	Au
Material	CuSn/CrNi
<b>Environmental</b>	
IMDS	No
<b>Other Features</b>	
Type	Male
Crimping Tool	65200411
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

**Direct Links** ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

**Services** ...

- Contact us
- Distributor list
- Pricing request
- Order samples

**Literature** ...

- Brochures & catalogs
- Product documentation
- Technical library

[Back > 60100631](#)

[Assistant](#)



**60100631**

**DCS-2 male 1.5 mm terminal**

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#)  [Print Datasheet](#)

**FCI Brings You More**

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

**Specifications**

General Dimensional Electrical Mechanical Physical Environmental Other Features

**General**

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

**Dimensional**

Contact Pitch	4 mm
---------------	------

**Electrical**

Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	21
Resistance (Contact)	< 2
<b>Mechanical</b>	
Range of Wire Gauge Min - Max	0.5 - 1 mm <sup>2</sup>
Contact mating force	< 7N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
<b>Physical</b>	
Plating	Sn
Material	CuFe/CrNi
<b>Environmental</b>	
IMDS	No
<b>Other Features</b>	
Type	Male
Crimping Tool	65200412
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

**Direct Links** ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

**Services** ...

- Contact us
- Distributor list
- Pricing request
- Order samples

**Literature** ...

- Brochures & catalogs
- Product documentation
- Technical library

[Back > 60100634](#)

[Assistant](#)



**60100634**

**DCS-2 male 1.5 mm terminal**

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#)  [Print Datasheet](#)

**FCI Brings You More**

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

**Specifications**

General Dimensional Electrical Mechanical Physical Environmental Other Features

**General**

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

**Dimensional**

Contact Pitch	4 mm
---------------	------

**Electrical**

Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	21
Resistance (Contact)	< 2
<b>Mechanical</b>	
Range of Wire Gauge Min - Max	0.5 - 1 mm <sup>2</sup>
Contact mating force	< 7N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
<b>Physical</b>	
Plating	Au
Material	CuFe/CrNi
<b>Environmental</b>	
IMDS	No
<b>Other Features</b>	
Type	Male
Crimping Tool	65200410
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

- Direct Links**
  - Cross Reference
  - RoHS/LF P/N search
  - Document & Drawing search
  - Application tooling
- Services**
  - Contact us
  - Distributor list
  - Pricing request
  - Order samples
- Literature**
  - Brochures & catalogs
  - Product documentation
  - Technical library

[Back > 60100641](#)

[Assistant](#)



**60100641**

**DCS-2 male 1.5 mm terminal**

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#)  [Print Datasheet](#)

**FCI Brings You More**

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

**Specifications**

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

**General**

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

**Dimensional**

Contact Pitch	4 mm
---------------	------

**Electrical**

Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	24
Resistance (Contact)	< 2
<b>Mechanical</b>	
Range of Wire Gauge Min - Max	> 1 - 1.5 mm <sup>2</sup>
Contact mating force	< 7N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
<b>Physical</b>	
Plating	Sn
Material	CuFe/CrNi
<b>Environmental</b>	
IMDS	No
<b>Other Features</b>	
Type	Male
Crimping Tool	65200411
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

- Direct Links** ...
  - Cross Reference ✕
  - RoHS/LF P/N search 🌱
  - Document & Drawing search
  - Application tooling
- Services** ...
  - Contact us
  - Distributor list
  - Pricing request
  - Order samples
- Literature** ...
  - Brochures & catalogs
  - Product documentation
  - Technical library

[Back > 60100711](#)

[Assistant](#)



**60100711**

**DCS-2 male 1.5 mm terminal**

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#)  [Print Datasheet](#)

**FCI Brings You More**

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

**Specifications**

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

**General**

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

**Dimensional**

Contact Pitch	4 mm
---------------	------

**Electrical**



Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	16
Resistance (Contact)	< 2
<b>Mechanical</b>	
Range of Wire Gauge Min - Max	0.2 - 0.35 mm <sup>2</sup>
Contact mating force	< 7N
Single Wire Seal Compatible	Yes
Contact unmating force	< 4N
<b>Physical</b>	
Plating	Sn
Material	CuSn/CrNi
<b>Environmental</b>	
IMDS	No
<b>Other Features</b>	
Type	Male
Crimping Tool	65200414
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

- Direct Links**
  - Cross Reference
  - RoHS/LF P/N search
  - Document & Drawing search
  - Application tooling
- Services**
  - Contact us
  - Distributor list
  - Pricing request
  - Order samples
- Literature**
  - Brochures & catalogs
  - Product documentation
  - Technical library

[Back > 60100714](#)

[Assistant](#)



**60100714**

**DCS-2 male 1.5 mm terminal**

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#)  [Print Datasheet](#)

**FCI Brings You More**

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

**Specifications**

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

**General**

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

**Dimensional**

Contact Pitch	4 mm
---------------	------

**Electrical**

Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	16
Resistance (Contact)	< 2
<b>Mechanical</b>	
Range of Wire Gauge Min - Max	0.2 - 0.35 mm <sup>2</sup>
Contact mating force	< 7N
Single Wire Seal Compatible	Yes
Contact unmating force	< 4N
<b>Physical</b>	
Plating	Au
Material	CuFe/CrNi
<b>Environmental</b>	
IMDS	No
<b>Other Features</b>	
Type	Male
Crimping Tool	65200414
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

- Direct Links**
  - Cross Reference
  - RoHS/LF P/N search
  - Document & Drawing search
  - Application tooling
- Services**
  - Contact us
  - Distributor list
  - Pricing request
  - Order samples
- Literature**
  - Brochures & catalogs
  - Product documentation
  - Technical library

[Back > 60100731](#)

[Assistant](#)



**60100731**

**DCS-2 male 1.5 mm terminal**

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#)  [Print Datasheet](#)

**FCI Brings You More**

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

**Specifications**

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

**General**

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

**Dimensional**

Contact Pitch	4 mm
---------------	------

**Electrical**

Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	2
Resistance (Contact)	< 2
<b>Mechanical</b>	
Range of Wire Gauge Min - Max	0.5 - 1 mm <sup>2</sup>
Contact mating force	< 7N
Single Wire Seal Compatible	Yes
Contact unmating force	< 4N
<b>Physical</b>	
Plating	Sn
Material	CuSn/CrNi
<b>Environmental</b>	
IMDS	No
<b>Other Features</b>	
Type	Male
Crimping Tool	65200415
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

- Direct Links** ...
- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling
- Services** ...
- Contact us
- Distributor list
- Pricing request
- Order samples
- Literature** ...
- Brochures & catalogs
- Product documentation
- Technical library

[Back > 60100734](#)

[Assistant](#)



**60100734**

**DCS-2 male 1.5 mm terminal**

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#)  [Print Datasheet](#)

**FCI Brings You More**

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

**Specifications**

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

**General**

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

**Dimensional**

Contact Pitch	4 mm
---------------	------

**Electrical**

Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	2
Resistance (Contact)	< 2
<b>Mechanical</b>	
Range of Wire Gauge Min - Max	0.5 - 1 mm <sup>2</sup>
Contact mating force	< 7N
Single Wire Seal Compatible	Yes
Contact unmating force	< 4N
<b>Physical</b>	
Plating	Au
Material	CuFe/CrNi
<b>Environmental</b>	
IMDS	No
<b>Other Features</b>	
Type	Male
Crimping Tool	65200413
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

- Direct Links**
  - Cross Reference
  - RoHS/LF P/N search
  - Document & Drawing search
  - Application tooling
- Services**
  - Contact us
  - Distributor list
  - Pricing request
  - Order samples
- Literature**
  - Brochures & catalogs
  - Product documentation
  - Technical library

[Back > 60100741](#)

[Assistant](#)



**60100741**

**DCS-2 male 1.5 mm terminal**

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#)  [Print Datasheet](#)

**FCI Brings You More**

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

**Specifications**

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

**General**

Product Type	Terminal System
Terminal size (in mm)	1.5
Family	DCS-2
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

**Dimensional**

Contact Pitch	4 mm
---------------	------

**Electrical**



Current Carrying Capacity at 23°C	20A
Current Carrying Capacity at 85°C	15A
Current Carrying Capacity at 100°C	10A
Maximum Insulation (in mm)	24
Resistance (Contact)	< 2
<b>Mechanical</b>	
Range of Wire Gauge Min - Max	> 1 - 1.5 mm <sup>2</sup>
Contact mating force	< 7N
Single Wire Seal Compatible	Yes
Contact unmating force	< 4N
<b>Physical</b>	
Plating	Sn
Material	CuSn/CrNi
<b>Environmental</b>	
IMDS	No
<b>Other Features</b>	
Type	Male
Crimping Tool	65200414
Tradename	DCS
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.