




Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Receptacle**

Connector System: **Wire-to-Board**

Number of Positions: **6**

Centerline (Pitch): **6.35 mm [.25 in]**

Features

Product Type Features

Rectangular Power Connector Type	Header
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	6
PCB Mount Orientation	Vertical
Number of Power Positions	6
Number of Rows	2

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features

Contact Layout	Matrix
----------------	--------



Multiple Contact Types	Without
Contact Current Rating (Max)	12 A
Contact Retention Within Housing	Without
Contact Type	Pin
PCB Contact Termination Area Plating Material	Pre-Tin
Contact Mating Area Plating Material	Pre-Tin
Contact Mating Area Plating Material Thickness	3.81 – 5.08 µm[150 – 200 µin]

Termination Features

Termination Post & Tail Length	3.81 mm[.15 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

Mechanical Attachment

Strain Relief	Without
Mating Alignment Type	Polarization
Mating Alignment	With
PCB Mount Alignment	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Connector Mounting Type	Board Mount
Mating Retention	With
Mating Retention Type	Positive Lock

Housing Features

Centerline (Pitch)	6.35 mm[.25 in]
Housing Color	Natural
Housing Material	Nylon

Dimensions

Row-to-Row Spacing	6.35 mm[.25 in]
PCB Thickness (Recommended)	1.57 – 2.36 mm[.062 – .093 in]

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Assembly Integration Feature	Without
Circuit Application	Power



Industry Standards

UL Flammability Rating	UL 94V-2
Glow Wire Rating	Standard Part - Not Glow Wire
Agency/Standard Number	E28476
Agency/Standard	UL
UL Rating	Recognized
VDE Tested	Yes

Packaging Features

Packaging Method	Bag
Packaging Quantity	100

Other

For Use With	Mates with Plug Housing (Using Socket Contacts)
--------------	---

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C





Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on



requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts


 TE Part # 350431-4 06P UMNL PINHDR ASSY V2 NAT LF	 TE Part # 350732-1 06P UMNL PIN HDR ASSY 94VO	 TE Part # 350586-1 09P UMNL PIN HDR ASSY V2 NATL	 TE Part # 350585-1 06P UMNL PIN HDR ASSY V2 NATL
 TE Part # 350432-1 09P UMNL PIN HDR ASSY NATL	 TE Part # 350434-1 15P UMNL PIN HDR ASSY NATL	 TE Part # 1586860-1 06P UMNL CAP HSG, GW	 TE Part # 350431-1 06P UMNL PIN HDR ASSY V2 NAT
 TE Part # 926682-3 06P UNIV.M-N-L.HSG.	 TE Part # 643423-1 06P UMNL HDR ASSY POL	 TE Part # 794536-1 06P UMNL CAP HSG 150C BLK	 TE Part # 350588-1 15P UMNL PIN HDR ASSY V2 NATL
 TE Part # 926682-1 UNIVERSAL M-N-L CAP 6 POS	 TE Part # 641969-1 06P UMNL PIN HDR ASSY V2 NATL	 TE Part # 1586887-1 06P UMNL CAP HSG, P/M, GW	 TE Part # 8-794536-1 06P UMNL CAP HSG 150C BLK, SPE



TE Part # 926682-4
6P UN-MNL AUFN-GEH



TE Part # 1586090-1
06P UMNL PINHDR NO DRAIN HOLE



TE Part # 1586090-3
06P UMNL PINHDR W/O DR HOLE LF



TE Part # 1586979-1
06P UMNL PIN HDR ASSY V2, GW

Also in the Series | Universal MATE-N-LOK



Circular Power Connectors(2)



Connector Contacts(11)




Insertion & Extraction Tools(4)




Power Contacts(207)



Rectangular Boots & Strain Relief(35)



Rectangular Connector Adapters(7)



Rectangular Connector Hardware(1)




Rectangular Connector Housings(2)



Rectangular Connector Keying Plugs(3)



Rectangular Connector Locking(4)



Rectangular Connector Seals(26)




Rectangular Power Connectors(729)


Customers Also Bought



TE Part #5-534237-2
04 MODII VRT SR CE 100/115




TE Part #4-2176307-2
RP 1E 0.1W 33K2 0.1% 25PPM 5K RL



TE Part #5-2176307-5
RP 1E 0.1W 45K3 0.1% 25PPM 5K RL



TE Part #2-1649329-1
RTE44009



Documents

Product Drawings

06P UMNL HDR ASSY W/O DRNS

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_643749-1_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_643749-1_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_643749-1_D.3d_stp.zip

English

Customer View Model

ENG_CVM_643749-1_E.3d_igs.zip

English

Customer View Model

ENG_CVM_643749-1_E.3d_stp.zip

English

Customer View Model

ENG_CVM_643749-1_E.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY

English

Product Specifications

Application Specification

English



Product Environmental Compliance

Product Compliance

English

Product Compliance

English