

PCB TERMINALS

















PRODUCT DRAWING



3D PDF



TERM., AMP-BARREL, 0.125, CLEANED

FASTON | Special Purpose Terminals

552699-4

TE Internal Number: 552699-4 Alias ID: 426391-000, TRMNL-IDC-1POS-LOOSE-PC

Always EU RoHS/ELV Compliant

PCB Thickness (Recommended) 1.57 – 2.39 mm [.062 – .094 in]

PCB Hole Diameter 1.55 – 1.65 mm [.061 – .065 in]

Wire Insulation Diameter (Max) 2.2 mm [.086 in]

Wire Size (AWG) 28 - 18

Wire Size (mm²) .08 - .9

Product Drawings

TERMINAL, AMP BARREL, .125 DIA

PDF **English**

CAD Files

3D PDF

PDF English

Customer View Model

2D_DXF.ZIP English

Customer View Model

3D_IGS.ZIP English

Customer View Model

3D STP.ZIP English

Catalog Pages/Data Sheets

PRINTED CIRCUIT BOARD TERMINALS AND DISCONNECTS

PDF **English**

Product Specifications

Application Specification

AMP-BARREL Terminals

PDF **English**

AMP-BARREL Terminals

English

Product Environmental Compliance

TE Material Declaration

MD_552699-4_12122015027_dmtec

PDF English

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Wire Cutoff Applies To	No Printed Circuit Board
Configuration Features	Wires per Terminal	1, 2
3ody Features	Plating Material	Pre-Tin
Contact Features	Contact Plating Material	Tin
Dimensions	PCB Thickness (Recommended)	1.57 – 2.39 mm [.062 – .094 in]
	PCB Hole Diameter Wire Insulation Diameter (Max)	1.55 – 1.65 mm [.061 – .065 in] 2.2 mm [.086 in]
	Wire Size (AWG)	28 – 18
	Wire Size (mm²)	.08 – .9
Packaging Features	Packaging Method	Tub
	Packaging Quantity	7500
Other	Comment	Accepts two wires of the same type that may vary in size by one wire gage.
Product Compliance	Statement of Compliance	

PDF

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT

