#### **AMP**

TE Internal #: 66255-1

Power Contacts, Contact, Tin-Lead, 14-12 AWG / 16 AWG Wire Size, 1.25-1.4 mm² / 2-3 mm² Wire Size, Wire-to-Wire, Wire &

Cable, Crimp, Power, Tab

View on TE.com >



Connectors > Power Connectors > Power Contacts



Power Contact Type: Contact

Contact Mating Area Plating Material: Tin-Lead

Wire Size: 1.25 – 1.4 mm², 2 – 3 mm²
Connector System: Wire-to-Wire

### **Features**

### **Product Type Features**

| Power Contact Type                | Contact      |
|-----------------------------------|--------------|
| Connector System                  | Wire-to-Wire |
| Connector & Contact Terminates To | Wire & Cable |

### **Electrical Characteristics**

| Test Current | 15 A |  |
|--------------|------|--|
|              |      |  |

### **Contact Features**

| Contact Mating Area Plating Material                  | Tin-Lead         |
|---|------------------|
| Contact Current Rating (Max)                          | 15 A             |
| Contact Type  | Tab              |
| Mating Tab Width                                      | 5.84 mm[.23 in]  |
| Mating Tab Thickness                                  | 2.67 mm[.105 in] |
| Contact Base Material                                 | Copper           |
| Contact Mating Area Plating Material Thickness        | 1.27 μm[50 μin]  |
| Wire Contact Termination Area Plating Thickness       | 1.27 μm[50 μin]  |
| Wire Contact Termination Area Plating Material        | Tin-Lead         |
| Wire Contact Termination Area Plating Material Finish | Bright           |
| Contact Orientation                                   | Right Angle      |
| Contact Underplating Material                         | Copper           |

### **Termination Features**



| Termination Method to Wire & Cable     | Crimp   |  |  |  |
|--|---|--|--|--|
| Mechanical Attachment                  |   |  |  |  |
| Wire Insulation Support                | With  |  |  |  |
| Dimensions                             |   |  |  |  |
| Wire Size                              | 1.25 – 1.4 mm², 2 – 3 mm²                                   |  |  |  |
| Accepts Wire Insulation Diameter Range | 3.43 – 4.06 mm[.135 – .16 in]                               |  |  |  |
| Usage Conditions                       |   |  |  |  |
| Operating Temperature Range            | -40 - 85 °C[-40 - 185 °F]                                   |  |  |  |
| Operation/Application                  |   |  |  |  |
| Circuit Application                    | Power   |  |  |  |
| Packaging Features                     |   |  |  |  |
| Packaging Method                       | Reel  |  |  |  |
| Packaging Quantity                     | 1500  |  |  |  |
| Other                                  |   |  |  |  |
| Wire/Cable Type                        | Discrete Wire   |  |  |  |
| For Use With                           | CPC Connectors, G Series Connectors, M<br>Series Connectors |  |  |  |

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Not Compliant  |
|---|--|
| EU ELV Directive 2000/53/EC                   | Not Compliant  |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Pb (13% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content                               | BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.   |
| Solder Process Capability                     | Not applicable for solder process capability   |

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



TE Part # 206037-2 CPC PLUG ASSEMBLY SIZE 17-3



TE Part # 90382-2 HHHT TYPE XII 16-12 ASSY



TE Part # 7-1579008-6
UNLOCKING TOOL





TE Part # 2-2151426-2 OCEAN\_2.0\_APPLICATOR-S-140F210O




TE Part # 2151426-2 OCEAN\_2.0\_APPLICATOR-S-140F210O



TE Part # 7-2151426-2

OCEAN\_2.0\_APPLICATOR-S140F210O



TE Part # 7-2151426-7

OCEAN\_2.0\_SPARE\_PART\_KIT140F210O




Customers Also Bought


















TE Part #6469078-1 HMZD 2PAIR HDR ASSY, 50MM MODU



TE Part #064126-000 TTMS-4.8-2

### **Documents**

### **Product Drawings**

MALE CONTACT ASSY. (STRIP)

English

### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_66255-1\_AE.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_66255-1\_AE.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_66255-1\_AE.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

AMP Circular Connectors for Commercial Signal & Power Applications

English

**Power Contacts** 

English

M\_SERIES\_PIN\_AND\_SOCKET\_CONNECTORS

English

Products for Aerospace and Defense

English

Power Contacts, Contact, Tin-Lead, 14-12 AWG / 16 AWG Wire Size, 1.25-1.4 mm² / 2-3 mm² Wire Size, Wire-to-Wire, Wire & Cable, Crimp, Power, Tab



Product Specifications

Application Specification

English