




LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION	DATE	DMN	APVD		
A		RLSD -17 THRU -24 PER EC 0730-0050-96	3-29-96	JH	RS		




- 1. POST TO WITHSTAND 13 NEWTONS (3LBS.) MIN. AXIAL FORCE IN BOTH DIRECTIONS SHOWN WITHOUT DISLODGING.
- 2. TOLERANCES APPLY TO SOLDER SIDE OF BOARD.
- 3. MEASURED AT SURFACE \square -A-
- 4. PLASTIC FLASH PERMITTED IN THIS AREA.
- 5. PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109-11-2.
- 6. ONE HOLE MAY BE UNDERSIZED (.065/.060 DIA.) FOR ASSEMBLY RETENTION DURING WAVE SOLDERING.
- 7. MATERIAL: HEADER-THERMOPLASTIC POLYESTER NON-FILLED 94V-0 (NATURAL) POST-COPPER ALLOY (SEE NOTES 13 & 14 FOR PLATING)
- 8. COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.
- 9. PLASTIC BURRS CAUSED BY CUT-OFF TOOLING ARE PERMITTED WITHIN THE MAXIMUM TOLERANCE ENVELOPE.
- 10. POST TO BE MEASURED WHEN STRIP IS HELD FLAT.
- 11. POST MUST WITHSTAND TWO 90° BENDS AGAINST EXTRUSION WITHOUT BREAKING.
- 12. DIMENSION SHOULD BE .175 MIN WHEN MATING WITH A MTA 156 CONNECTOR ASSEMBLY OR A SL-156 CONNECTOR ASSEMBLY.
- 13. GOLD PLATE AREA, .000015 MIN., ALL SIDES, OVER NICKEL UNDERPLATE, .000050 MIN., ALL SIDES AND ENTIRE LENGTH OF POST.
- 14. BRIGHT TIN/LEAD (93/7) PLATE AREA, .000150-.000350 THICK, ALL FOUR SIDES, .175 MIN.

3.744	95.10	24	2-644766-4
3.588	91.14	23	2-644766-3
3.432	87.17	22	2-644766-2
3.276	83.21	21	2-644766-1
3.120	79.25	20	2-644766-0
2.964	75.29	19	1-644766-9
2.808	71.32	18	1-644766-8
2.652	67.36	17	1-644766-7
2.496	63.40	16	1-644766-6
2.340	59.44	15	1-644766-5
2.184	55.47	14	1-644766-4
2.028	51.51	13	1-644766-3
1.872	47.55	12	1-644766-2
1.716	43.59	11	1-644766-1
1.560	39.62	10	1-644766-0
1.404	35.66	9	644766-9
1.248	31.70	8	644766-8
1.092	27.74	7	644766-7
.936	23.77	6	644766-6
.780	19.81	5	644766-5
.624	15.85	4	644766-4
.468	11.89	3	644766-3
.312	7.92	2	644766-2
IN	MM	NUMBER OF POSITIONS	PART NUMBER
L			

IN	MM	IN	MM
.063	1.60		25.40
.060	1.52	1.000	25.40
.045	1.14	.750	19.05
.030	0.76	.450	11.43
.015	0.38	.425	10.80
.012	0.30	.415	10.54
.010	0.25	.300	7.62
.008	0.20	.180	4.57
.005	0.13	.175	4.45
.001	0.03	.156	3.96
.000350	0.00889	.125	3.18
.000150	0.00381	.078	1.98
.000050	0.00127	.070	1.78
.000015	0.00038	.068	1.73
.000	0.00	.065	1.65
IN	MM	IN	MM

CONVERSION TABLE



RECOMMENDED MOUNTING HOLE PATTERN FOR .063 THICK P.C. BOARD



DIMENSIONS: INCHES TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PL ±.005 1 PL ±.005 2 PL ±.005 3 PL ±.005 4 PL ±.005 ANGLES FINISH		DWG L. SMITH 4-20-94 CHK R. SWING 4-20-94 APVD D. CLARK 5-06-94 NAME MTA-156 HEADER ASSEMBLY, FRICTION LOCK, STRAIGHT .045 SQUARE POST, .000015 GOLD, SPECIAL SIZE A1 CAGE CODE 00779 DRAWING NO. 644766 SCALE 5:1 SHEET 1 OF 1 REV A	AMP Incorporated Harrisburg, PA 17105-3608 CUSTOMER DRAWING
---	--	--	---