

HPI

TE Internal #: 6-440129-2

Housing, Receptacle, Wire-to-Board, 2 Position, 2 mm [.079 in]

Centerline, Crimp, 1 Row, Black, Mating Retention, Wire & Cable,

Power & Signal, HPI

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings > AMP HPI 2.0MM RECEPTACLE HOUSINGS











Connector Product Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 2

Centerline (Pitch): 2 mm [.079 in]

All AMP HPI 2.0MM RECEPTACLE HOUSINGS (60)

Features

Product Type Features

Connector Product Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	2	
Number of Rows	1	

Electrical Characteristics

Dielectric Withstanding Voltage (Max)	1000 VAC
Insulation Resistance	1000 ΜΩ
Operating Voltage	250 VAC



Contact Features	
Contact Layout	Inline
Contact Type	Socket
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	3 A
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Strain Relief	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Retention Type	Detent
Mating Retention	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Entry Configuration	Both Ends Closed
Housing Material	Thermoplastic
Centerline (Pitch)	2 mm[.079 in]
Housing Color	Black
Dimensions	
Connector Length	27.9 mm[1.098 in]
Connector Height	4.5 mm[.177 in]
Connector Width	6.9 mm[.272 in]
Accepts Wire Insulation Diameter Range	.9 – 1.5 mm[.035 – .059 in]
Wire Size	.05 – .22 mm²
Usage Conditions	
Operating Temperature Range	-25 – 85 °C[-13 – 185 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Glow Wire Rating	Standard Part - Not Glow Wire



UL Flammability Rating UL 94V-0

Packaging Features

Packaging Quantity	2000
Packaging Method	Bag/Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | HPI







Wire-to-Board Connector Assemblies & Housings(139)



Wire-to-Board Connector Contacts(2)

Customers Also Bought








TE Part #440129-6 AMP HPI 2.0MM RECEPTACLE HOUSINGS







Documents

Product Drawings

HPI 2.0MM,HSG,2POS,BLACK

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_6-440129-2_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6-440129-2_C.3d_igs.zip

English

Customer View Model

ENG_CVM_6-440129-2_C.3d_stp.zip

Housing, Receptacle, Wire-to-Board, 2 Position, 2 mm [.079 in] Centerline, Crimp, 1 Row, Black, Mating Retention, Wire & Cable, Power & Signal, HPI



English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

HPI Connectors QRG

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English