

6450870-8 ✓ ACTIVE

[MULTI-BEAM](#) | [MULTI-BEAM XLE](#)


TE Internal #: 6450870-8

Rectangular Power Connectors, Connector Assembly, Receptacle,  
Board-to-Board, 38 Position, MULTI-BEAM XLE

[View on TE.com >](#)



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Connector Assembly**

Connector & Housing Type: **Receptacle**

Connector System: **Board-to-Board**

Number of Positions: **38**

Centerline (Pitch): **2.54 mm, 2.92 mm, 6.35 mm [ .1 in, .115 in, .25 in ]**

## Features

### Product Type Features

Assembly Requirement	Factory Assembled
Rectangular Power Connector Type	Connector Assembly
Connector & Housing Type	Receptacle
Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board

### Configuration Features

Mating & Unmating Configuration	Normal
Number of Positions	38
PCB Mount Orientation	Right Angle
Number of Power Positions	6
Number of Signal Positions	32
Number of Rows	4

### Electrical Characteristics

Operating Voltage	60 VDC, 200 VDC
-------------------	-----------------

### Contact Features

Power Contact Base Material	Tin
Contact Current Rating (Max)	42 A
Contact Retention Within Housing	Without
Contact Type	Receptacle



PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Noble Metal
Contact Mating Area Plating Material Thickness	.76 $\mu\text{m}$ [30 $\mu\text{in}$ ]
Underplate Material Thickness	3.43 $\mu\text{m}$

### Termination Features

Termination Post & Tail Length	3.43 mm[.135 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

### Mechanical Attachment

PCB Mount Retention	With
PCB Mount Retention Type	Boardlock
Connector Mounting Type	Board Mount
Mating Retention Type	Boardlock

### Housing Features

Centerline (Pitch)	2.54 mm, 2.92 mm, 6.35 mm[.1 in][.115 in][.25 in]
Housing Color	Black
Housing Material	High Temperature Thermoplastic

### Dimensions

Row-to-Row Spacing	2.54 mm[.1 in]
--------------------	----------------

### Usage Conditions

Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
-----------------------------	----------------------------

### Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

### Industry Standards

UL Flammability Rating	UL 94V-0
Glow Wire Rating	High Temperature Part - Not Glow Wire

### Packaging Features

Packaging Method	Tray
------------------	------

### Other

Wire Color	Black
------------	-------

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

## Compatible Parts





Also in the Series | [MULTI-BEAM XLE](#)



Rectangular Power Connectors(109)

## Customers Also Bought

TE Part #1-5177983-3  
0.8FH,R05H.5,080,15/Sn,TUTE Part #1982198-1  
INV.MOD.JACK,4/4POS,HANDSET SMTE Part #1734580-8  
MOD-Jack,RJ45,10P8C,SHD LP, HDT,  
50u" AuTE Part #1775133-2  
MOD JACK, RJ45, MULTIPLE, 1X4,  
15u" AuTE Part #1888669-5  
AssmDDR2VLPDimmSolderTailVerticalTE Part #4-6450831-7  
MBXL R/A HDR12S+2P+12LPTE Part #5-1977909-2  
12P,2.0MM HDR. PIN 12 OMITTED,  
2.1 LEADSTE Part #5-6450831-9  
MBXL R/A HDR12S+2P+12LPTE Part #5767178-2  
MICTOR .355 RECEPTACLE, 76 POS  
T&R PACKATE Part #6450820-3  
MBXL VERT HDR 3P+32S+3P

## Documents

### Product Drawings

[MBXLE R/A RCPT 3P+32S+3P](#)

English

### CAD Files

[3D PDF](#)

[3D](#)

### Customer View Model

[ENG\\_CVM\\_CVM\\_6450870-8\\_D2\\_c-6450870-8-d2.2d\\_dxf.zip](#)



English

**Customer View Model**

[ENG\\_CVM\\_CVM\\_6450870-8\\_D2\\_c-6450870-8-d2.3d\\_igs.zip](#)

English

**Customer View Model**

[ENG\\_CVM\\_CVM\\_6450870-8\\_D2\\_c-6450870-8-d2.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

---

**Datasheets & Catalog Pages**

[POWER\\_CONNECTORS\\_CATALOG\\_SEC01\\_BOARD\\_TO\\_BOARD](#)

English

[MULTI-BEAM XLE Connectors Quick Reference Guide](#)

English

[2\\_PIECE\\_POWER\\_CONNECTORS\\_qrg\\_4-1773458-1](#)

English

---

**Product Specifications**

[Application Specification](#)

English

---

**Product Environmental Compliance**

[TE Material Declaration](#)

English