

84533-6 ✓ ACTIVE

FPC

TE Internal #: 84533-6

FPC Connectors, Flex-to-Board, 6 Position, .049 in [1.25 mm]

Centerline, Non-ZIF, Right Angle, Through Hole - Solder, Height
4.8 mm [.189 in]

[View on TE.com >](#)



Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > FPC Connectors > 1.25mm FPC Connectors



Connector System: **Flex-to-Board**

Number of Positions: **6**

Centerline (Pitch): **1.25 mm [.049 in]**

Insertion Force Type: **Non-ZIF**

PCB Mount Orientation: **Right Angle**

[All 1.25mm FPC Connectors \(65\)](#)

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Receptacle
Connector Product Type	Connector Assembly
Connector System	Flex-to-Board
Insertion Force Type	Non-ZIF
Sealable	No
Connector & Contact Terminates To	Flexible Printed Circuit (FPC), Printed Circuit Board

Configuration Features

Compatible With Wire & Cable Type	FFC, FPC
Number of Rows	1
Number of Positions	6
PCB Mount Orientation	Right Angle

Electrical Characteristics



Operating Voltage	50 VAC
-------------------	--------

Contact Features

Contact Layout	Staggered Type A
----------------	------------------

PCB Contact Termination Area Plating Material Thickness	.8 μm [31.49 μin]
---	--

Contact Type	Socket
--------------	--------

Contact Mating Area Plating Material Thickness	.8 μm [31.49 μin]
--	--

PCB Contact Termination Area Plating Material Finish	Bright
--	--------

Contact Shape & Form	Single Beam
----------------------	-------------

Contact Mating Area Plating Material Finish	Bright
---	--------

PCB Contact Termination Area Plating Material	Tin
---	-----

Contact Base Material	Phosphor Bronze
-----------------------	-----------------

Contact Mating Location	Top
-------------------------	-----

Contact Mating Area Plating Material	Tin
--------------------------------------	-----

Contact Current Rating (Max)	1 A
------------------------------	-----

Termination Features

Termination Post & Tail Length	3.2 mm[.126 in]
--------------------------------	-----------------

Termination Method to Printed Circuit Board	Through Hole - Solder
---	-----------------------

Mechanical Attachment

Mating Alignment	With
------------------	------

PCB Mount Retention Type	Kinked Solder Tails
--------------------------	---------------------

PCB Mount Alignment	With
---------------------	------

PCB Mount Retention	With
---------------------	------

Connector Mounting Type	Board Mount
-------------------------	-------------

Housing Features

Housing Material	PBT GF
------------------	--------

Housing Color	White
---------------	-------

Centerline (Pitch)	1.25 mm[.049 in]
--------------------	------------------

Dimensions

Connector Length	11.25 mm[.443 in]
------------------	-------------------

PCB Thickness (Recommended)	1.6 mm[.063 in]
-----------------------------	-----------------

Connector Height	4.8 mm[.189 in]
------------------	-----------------

Connector Width	8.8 mm[.346 in]
-----------------	-----------------



Accepts Flex Cable Thickness	.3 mm[.012 in]
------------------------------	----------------

Usage Conditions

Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]
-----------------------------	---------------------------

Operation/Application

Circuit Application	Signal
---------------------	--------

Identification Marking

Circuit Identification Feature	With
--------------------------------	------

Packaging Features

Packaging Quantity	290
--------------------	-----

Packaging Method	Tray
------------------	------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------

EU ELV Directive 2000/53/EC	Compliant
-----------------------------	-----------

China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
---	---

EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
--	---

Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
-----------------	--

Solder Process Capability	Wave solder capable to 265°C
---------------------------	------------------------------


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 84534-6
1.25MM FFC POST PLATED V 6P




TE Part # 1734803-6
FPC Non Zif 1.25mm 6P R/A

Customers Also Bought



TE Part #3-2176070-2
3521 200R 1% 2W



TE Part #1776260-8
Bd Mt Screwless, 5.08mm Top Wi




TE Part #5-1393144-1
K10P-11DT5-24=K10/K20




TE Part #1734248-7
1.0 FPC, ZIF V/T, SMT, 7P



TE Part #2-2176304-2
RP 1E 0.1W 16R5 0.1% 25PPM 5K RL




TE Part #2176306-9
RP 1E 0.1W 1K4 0.1% 25PPM 5K RL




TE Part #6-2176363-7
RQ 0402 2K1 0.1% 10PPM 5K RL



TE Part #1393304-9
V23134J1052D642-EV-CBOX



TE Part #8-1768033-6
LEB-1336P-8A



TE Part #5-1768033-7
LEB-0916P-8A

Documents

Product Drawings

1.25MM FFC POST PLATED H 6P

English

CAD Files

Customer View Model

ENG_CVM_CVM_84533-6_E.2d_dxf.zip

English

3D PDF



3D

Customer View Model

[ENG_CVM_CVM_84533-6_E.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_84533-6_E.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[1-1773959-6-flexible-printed-circuit-con](#)

English

[1-1773959-7-FPC-Connectors-CN](#)

[FPC Connector Family](#)

English

[5-1773461-0_Standard_FPC_Connector_Quick_Reference_Guide](#)

English

Product Specifications

[Product Specification](#)

English

Product Environmental Compliance

[TE Material Declaration](#)

English