
# 87191-2 - ACTIVE

#### AMP

TE Internal #: 87191-2 Connector Contact, Socket, Wire-to-Board, 30 – 28 AWG Wire Size, 100.5 – 159.8 CMA Wire Size, .05 – .09 mm<sup>2</sup> Wire Size, Tin, Loose Piece, Wire & Cable

#### View on TE.com >





Contact Type: **Socket** Connector System: **Wire-to-Board** Wire Size: **.05 – .09 mm<sup>2</sup>** 

#### Features

#### **Product Type Features**

	Connector System	Wire-to-Board		
	Connector & Contact Terminates To	Wire & Cable		
Electrical Characteristics				
	Termination Resistance	12 mΩ		



Insulation Resistance	5000 MΩ
Dielectric Withstanding Voltage (Max)	750 V
Operating Voltage	250 VAC
Contact Features	
Mating Square Post Dimension	.64 mm[.025 in]
	100 µin
Wire Contact Termination Area Plating Material	Tin-Lead
PCB Contact Termination Area Plating Material Finish	Bright
Contact Shape & Form	Square
Contact Mating Area Plating Material Finish	Bright
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Type	Socket
Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	3 A

### 87191-2

Connector Contact, Socket, Wire-to-Board, 30 – 28 AWG Wire Size, 100.5 – 159.8 CMA Wire Size, .05 – .09 mm<sup>2</sup> Wire Size, Tin, Loose Piece, Wire & Cable



#### **Termination Features**

Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Accepts Wire Insulation Diameter Range	.74 – .99 mm[.029 – .039 in]
Wire Size	.05 – .09 mm²
Usage Conditions	
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
Approved Standards	UL E28476
Packaging Features	
Packaging Quantity	1000
Packaging Method	Loose Piece

#### Other

Comment	(*) For use with Model "K" machines. Call the Technical Assistance Center (1-800-522- 6752) for any tooling questions., These
	contacts must be crimped per AMP
	Specification No. 114-25006 in order to
	function properly in a connector housing.

## Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU

EU ELV Directive 2000/53/EC

China RoHS 2 Directive MIIT Order No 32, 2016

EU REACH Regulation (EC) No. 1907/2006

#### Not Compliant

Not Compliant

Restricted Materials Above Threshold

Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Pb (13% in Component Part) Article Safe Usage Statements:

#### 87191-2

Connector Contact, Socket, Wire-to-Board, 30 – 28 AWG Wire Size, 100.5 – 159.8 CMA Wire Size, .05 – .09 mm<sup>2</sup> Wire Size, Tin, Loose Piece, Wire & Cable



Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Halogen Content


#### Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



TE Part # 368086-1 090II NON SLD TAB(SQ 2.0)

# **Customers Also Bought**



### Documents

Product Drawings LOCKING CLIP ASSY .025 SQ LP

English

CAD Files 3D PDF

**C** For support call+1 800 522 6752

#### 87191-2

Connector Contact, Socket, Wire-to-Board, 30 – 28 AWG Wire Size, 100.5 – 159.8 CMA Wire Size, .05 – .09 mm<sup>2</sup> Wire Size, Tin, Loose Piece, Wire & Cable



English **Customer View Model** ENG\_CVM\_87191-2\_J.3d\_igs.zip English Customer View Model ENG\_CVM\_87191-2\_J.3d\_stp.zip English Customer View Model ENG\_CVM\_87191-2\_J.2d\_dxf.zip English By downloading the CAD file I accept and agree to the **Terms and Conditions** of use. **Product Specifications Application Specification** English **Instruction Sheets** Instruction Sheet (U.S.) English AMPMODU Locking Clip Contacts and Housings for 0.64mm Square Posts English Instruction Sheet (U.S.)

English
Hand Crimping Tool 90295-1

English