TE Internal #: 965927-2

Splices, 24 – 20 AWG Wire Size, .2 – .5 mm² Wire Size, Serrated, 404

- 1022 CMA Wire Size, Copper Alloy, None, Cable Splice Splice,

Serrated

View on TE.com >



Terminals & Splices > Splices











Wire Size: .2 – .5 mm²

Sealable: No

Splice Features: Serrated

Accepts Wire Insulation Diameter Range: 1.15 – 1.6 mm [.045 – .062 in]

Features

Product Type Features

Barrel Style	Crimp
Sealable	No
Splice Type	Cable Splice
Serrated	Yes
Wire Insulation Support Retention Type	Insulation Support
71	

Configuration Features

Number of Serrations	3	
Compatible With Wire & Cable Type	FFC	

Electrical Characteristics

Operating Voltage	300 V
Current Rating	2 A

Body Features

Plating Thickness	2 – 4 μm[78.74 – 157.48 μin]
Plating Material	Tin
Splice Features	Serrated



Primary Product Material	Copper Alloy
Primary Product Color	None
Contact Features	
Barrel Type	Open
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Wire Size	404 – 1022 CMA
Accepts Wire Insulation Diameter Range	1.15 – 1.6 mm[.045 – .062 in]
Overall Product Length	12.3 mm[.484 in]
Usage Conditions	
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]
Industry Standards	
Government Qualified Splice	Yes
Packaging Features	

Product Compliance

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Reel

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as



EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought











TE Part #2282423-1 20POS,MCON 0.5 CB,REC HSG,ASSY, CODA









Documents

Product Drawings

SPLICE F.DRAHT+FFC

English

CAD Files

Customer View Model

ENG_CVM_CVM_965927-2_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_965927-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_965927-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Application Specification

English